






























Accessories				
	Items	Description	User Price	
<b>Switches</b>				
1	<a href="#">DS-3E0105P-E/M</a>	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af PoE power budget 35W	Call	
2	<a href="#">DS-3E0105P-E</a>	L2, Unmanaged, 4 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 58W	Call	
3	<a href="#">DS-3E0109P-E/M</a>	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af, PoE power budget 60W	Call	
4	<a href="#">DS-3E0109P-E</a>	L2, Unmanaged, 8 100M PoE port, 1 100M uplink port, 802.3af/at, PoE power budget 123W	Call	
5	<a href="#">DS-3E0318P-E</a>	L2, Unmanaged, 16 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 230W	Call	
6	<a href="#">DS-3E0326P-E</a>	L2, Unmanaged, 24 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 370W	Call	
7	<a href="#">DS-3E1310P-E</a>	L2, Web managed, 8 100M PoE port, 2 1000M combo port, 802.3af/at, PoE power budget 123W	Call	
8	<a href="#">DS-3E1318P-E</a>	802.3af/at PoE standard 8-core power supply technology, reducing the power circuit loss, Data monitor and control for the important ports, EXTEND mode available to extend the network cable transmission distance to 250 meters Buffer optimization to guarantee the video data transmission, VLAN configurable Port trunk, multicast and port mirroring, WEB management, Store-and-forward switching IEEE802.3, IEEE802.3u and IEEE802.3x network standards available MTBF (Mean Time Between Failure) ≥ 100,000 hours All-metal enclosed construction Table-mounted and rack-mounted design for convenient installation	Call	
<b>Cables</b>				
10	<a href="#">DS-1LN6-JE-W</a>	UTP / CAT.6 / Indoor PVC / 23AWG, Full 305m, OFC / 0.530mm, CM Rating, Default Color: BLUE. TEST FLUKE	IRR 46,940,000	
11	<a href="#">DS-1LN6-JU</a>	UTP / CAT.6 / Indoor PVC / 23AWG Full 305m OFC / 0.565mm CM Rating Default Color: Orange	IRR 51,660,000	
<b>Brackets</b>				
13	<a href="#">DS-1602ZJ</a>	Wall mount , Hik white , Aluminum alloy , 97×182×305mm Suitable for:- DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx DS-2DF7xxx-DS-2DF5xxx	IRR 12,000,000	
	<a href="#">DS-1208ZJ-DM21</a>		IRR 3,930,000	
	<a href="#">DS-1273ZJ-140</a>		IRR 7,280,000	

	<a href="#">DS-1272ZJ-110</a>		IRR 5,690,000	
14	<a href="#">DS-1602ZJ-pole</a>	Vertical pole mount, Hik white , Aluminum alloy , 117×194×310mm , Suitable for:DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx--DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	Call	
	<a href="#">DS-1604ZJ</a>		IRR 28,420,000	
	<a href="#">DS-1604ZJ-P</a>		IRR 28,420,000	
15	DS-1605ZJ	Wall Mount bracket Parameters: Wall mounting bracket-Colour: Hik White-Feature: Suitable for speed dome cameras Dimensions: Ø171.7 x 158 x 228.6mm	Call	
16	<a href="#">DS-1661ZJ -P</a>	Pendent Mounting Bracket In/Outdoor,-Color: -Hik white-Material: -Aluminum alloy-Dimensin: - 116.5×200mm-Weight: -600g	IRR 8,900,000	
17	<a href="#">DS-1662ZJ</a>	Pendant mount , Hik white , Aluminum alloy , Φ116.5×500mm Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS- 2DF5xxx	IRR 8,600,000	
18	<a href="#">DS-1663ZJ</a>	Ceiling mount , Hik white , Aluminum alloy , Φ116.5×57mm-Suitable for:-DS-2DE/AE4xxx DS-2DE/AE5xxx-DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	ناموجود	
19	<a href="#">DS-1693ZJ</a>	Wall mount , Hik white , steel , 190×200×500mm , 5700g Suitable for PTZ positioner	IRR 61,580,000	
	<a href="#">DS-1280ZJ-DM21</a>		IRR 4,610,000	
	<a href="#">DS-1697ZJ</a>		IRR 64,590,000	
	<a href="#">DS-2601ZJ</a>		IRR 20,720,000	
	<a href="#">DS-1671ZJ-SD11</a>		IRR 6,640,000	
20	<a href="#">DS-1681ZJ</a>	Ceiling mount , Hik white , Aluminum alloy -Suitable for:-DS-2DE/AE4xxx-DS-2DE/AE5xxx DS-2DE/AE7xxx-DS-2DF8xxx-DS-2DF6xxx-DS-2DF7xxx-DS-2DF5xxx	IRR 2,640,000	
21	<a href="#">DS-1273ZJ-135B</a>	Wall mount , White , Aluminum alloy , with junction box , Φ135×182×120mm Suitable for: DS-2CD27xx	Call	
22	Keyboard			

23	DS-1100KI	Network Keyboard, 7" TFT touch screen, up to 256 units of DVR/Network Cameras/Speed Dome management, 1-ch HD 1080p video steam decoding, USB 2.0 interface for video backup	Call	
24	DS-1005KI	network Keyboard, USB interface, support Hikvision VMS, NVR, DVR	Call	
25	<b>Tester</b>			
26	<a href="#">IPC-4300H</a>	IPC-4300 IP camera tester 4.3 inch capacitive touch screen / ONVIF/ Hikvision, Dahua, etc more than 40 IP camera brands test /IP Camera view /12 V/2A power output / 5V 2A power bank / PoE power supply / HDMI output / WIFI	Call	
27	DS-TT-X41T-tester	TurboHD (HD-TVI 2.0), HDMI 1.0, VGA, and CVBS Inputs - 7" TFT active matrix LCD monitor - TurboHD: Up to 720p @ 25/30/50/60 fps, 1080p @ 25/30 fps	IRR 138,420,000	
28	<b>POE INJECTOR</b>			
	DS-POE-60W ULTRA INJECTOR	Hikvision DS-POE-60W PoE Injector for Hikvision PTZ.	IRR 19,000,000	
	<b>Adapters</b>			
29	AD-121/P	12V-1A	IRR 420,000	
30	AD-122/P	12V -2A	IRR 450,000	
31	AD-122/PL	12V-2A	IRR 480,000	
32	AD-125/PL	12V -5A	IRR 800,000	
33	AD-12A/M	12V -10A-METAL	IRR 1,180,000	
34	AD-12F/M	12V -15A-METAL	IRR 1,600,000	
35	AD-12K/MF	12V -20A-METAL WITH FAN	IRR 1,840,000	
36	AD-12U/MF	12V -30A-METAL WITH FAN	IRR 2,550,000	

D.D.C PERSIA  
TelFax : 98 21 88 54 18 00  
98 21 88 55 55 58  
98 21 88 10 20 01 - 5  
www.ddcpersia.com  
info@ddcpersia.com