

















































NAS Storage				
Items	Description	User Price		
<b>Rackmount Series</b>				
<b>30-bay</b>				
1	<a href="#">TES-3085U-D1548-16GR</a>	Intel® Xeon® Processor D-1548, 8-core 2.0 GHz , 16GB ECC DDR4 (Max. 128GB) ,SAS 12Gb/s, SAS 6Gb/s, SATA 6Gb/s , Single, JBOD, 0, 1, 5, 6, 10, 5+spare, 6+spare, 10+spare, Global hot spare , 4 GigaLan, built-in dual port 10G-bE SFP+, 40GbE ready , Dual OS (QTS / QES) Optional	call	
2	<a href="#">TS-h3088XU-RP-W1250-32G</a>	Intel® Xeon® W-1250 6-core 3.3 GHz processor (boost up to 4.7 GHz) - System Memory: 32 GB UDIMM DDR4 ECC (2 x 16 GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: Front: 24 x 2.5-inch SATA 6Gb/s, 3Gb/s & Rear: 6 x 2.5-inch SATA 6Gb/s, 3Gb/s - 25 Gigabit Ethernet Port: 2 - USB 3.2 Gen 2 (10Gbps) Port: 2 x Type-C USB 3.2 Gen 2 10Gbps & 2 x Type-A USB 3.2 Gen 2 10Gbps - HDMI Output: 1, HDMI 1.4b (up to 4096 x 2160 @ 30Hz)	call	
<b>24-bay</b>				
4	<a href="#">TS-h2490FU-7232P-64G</a>	AMD EPYC™ 7232P 8-core 3.1 GHz processor (up to 3.2 GHz) - System Memory: 64 GB RDIMM DDR4 ECC (8 x 8 GB) - Maximum Memory: 4 TB (16 x 256 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 24 x 2.5-inch U.2 PCIe NVMe - Drive Compatibility: 2.5-inch U.2 NVMe Gen 3 x4 solid state drives - 25 Gigabit Ethernet Port: 2 x 25GbE SFP28 SmartNIC port - USB 3.2 Gen 1 port: 2	call	
5	<a href="#">TS-2483XU-RP-E2136-16G</a>	Intel® Xeon® E-2136 6-core 3.3 GHz processor (burst up to 4.5 GHz) - System Memory 16 GB UDIMM DDR4 ECC (2 x 8GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 24 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen2 5V/1A	call	
7	<a href="#">TS-2477XU-RP-2600-8G</a>	AMD Ryzen™ 5 2600 6-core 3.4 GHz processor, Turbo Core 3.9 GHz - System Memory 8 GB UDIMM DDR4 (2 x 4GB) Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 24 x 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port 4	call	
8	<a href="#">TVS-2472XU-RP-i5-8G</a>	Intel® Core™ i5-8500 6-core 3.0 GHz Processor, Max turbo to 4.0 GHz - Graphic Processors Intel® UHD Graphics 630 - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 24 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps	call	
<b>20-bay</b>				
10	<a href="#">TDS-16489U-SB2</a>	Intel® Xeon® 8-core Processor E5-2630 v3 (20M Cache, 2.40 GHz) : (E5-2630 2.4GHz 8-core processor x2, 128GB DDR4 RDIMM) : USB 4 x USB 3.0 port : Hard Drive 16 x 3.5-inch SAS (12Gbps/6Gbps), SATA (6Gbps/3Gbps) hard drive, or 2.5-inch SAS/SATA SSD 4 x 2.5-inch SAS (12Gbps) SSD, or SAS/SATA (6Gbps/3Gbps) SSD : Maximized Raw Capacity 128 TB : Hard Drive Interface SAS 12Gb/s, backward compatible with SAS/SATA 6Gbps : 10/100/1000 Mbps LAN Port 2 : 10Gbps LAN Port 4 x SFP+ : PCIe Slot 4 (3 x PCIe Gen3 x8, 1 x PCIe Gen3 x16) : Power Supply 650W (Redundant power)	call	
11	<a href="#">TDS-16489U-SE1-R2</a>	Intel Xeon E5-2620 v4 8-core 2.1 GHz processor x2 - System Memory 64GB RDIMM DDR4 (8 x 8GB) - Maximum Memory RDIMM/LRDIMM: 1 TB (16 x 64 GB) - Flash Memory 4GB (DOM for dual OS) - Drive Bay Front: 16 x 3.5-inch Rear: 4 x 2.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 4 x 10GbE SFP+ - USB 3.0 port 4	call	
12	<a href="#">GM-1002</a>	Intel® Xeon® E-2236 6-core 3.4 GHz processor (burst up to 4.8 GHz) per node - System Memory: 16 GB UDIMM DDR4 (2 x 8 GB) per node - Maximum Memory: 128 GB (4 x 32 GB) per node - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 8 x 3.5-inch + 2 x 2.5-inch per node - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC (Mellanox ConnectX®-4 Lx EN) - USB 3.2 Gen 2 (10Gbps) Port: 4 x Type-A per node	call	
<b>18-bay</b>				










14	<a href="#">TS-h1886XU-RP-D1622-32G</a>	Intel® Xeon® D-1622 quad-core 2.60 GHz processor (burst up to 3.2 GHz) - System Memory: 32 GB UDIMM DDR4 ECC (2 x 16GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: Front: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s & Rear: 6 x 2.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port: 2	call	
15	<a href="#">TS-1886XU-RP-D1602-4G</a>	Intel® Xeon® D-1622 quad-core 2.60 GHz processor (burst up to 3.2 GHz) - System Memory: 4 GB UDIMM DDR4 ECC (1 x 4GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: Front: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s, Rear: 6 x 2.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port : 2	call	
16	<a href="#">TES-1885U-D1531-16GR</a>	Intel® Xeon® D-1622 quad-core 2.60 GHz processor (burst up to 3.2 GHz) - System Memory: 4 GB UDIMM DDR4 ECC (1 x 4GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: Front: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s, Rear: 6 x 2.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port : 2	call	
17	<a href="#">TES-1885U-D1521-8GR</a>	Intel® Xeon® D-1521 quad-core 2.4 GHz processor, Max turbo to 2.7 GHz Memory 8 GB RDIMM DDR4 ECC (1 x 8GB)-Maximum Memory UDIMM: 64 GB (4 x 16 GB) RDIMM: 128GB (4 x 32 GB) - Flash Memory 4GB (DOM for dual OS) - Drive Bay Front: 12 x 3.5-inch Rear: 6 x 2.5-inch- 10 Gigabit Ethernet Port 2 x 10G SFP+	call	
18	16-bay			
19	<a href="#">ES1686dc-2123IT-64G</a>	Intel® Xeon® D-2123IT 4-core 2.20 GHz processor (burst up to 3.0 GHz) per controller - System Memory 32 GB RDIMM DDR4 ECC (4x 8 GB) per controller - Maximum Memory 512 GB (8 x 64GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 16 x 3.5-inch - Cache for Copy To Flash (C2F) 1 per each controller (64GB) - Gigabit Ethernet Port (RJ45) 3 for each controller (one for remote management) - 10 Gigabit Ethernet Port 4 x 10GbE SFP+ for each controller - USB 3.2 Gen 1 port 2 per each controller	call	
20	<a href="#">ES1640dc-v2-E5-96G</a>	Intel Xeon 6-core Processor E5-2420 v2 (15M Cache, 2.20GHz) - System Memory 80 GB RDIMM DDR3 ECC (2 x 32 GB + 16 GB) per controller - Maximum Memory 80 GB (2 x 32 GB + 16 GB) - Flash Memory 2 GB - Drive Bay 16 x 3.5-inch - Cache for Copy To Flash (C2F) 1 per each controller (M.2 2280 SSD dedicated to NVRAM, SATA signaling) - Gigabit Ethernet Port (RJ45) 1 for each controller (for remote management) - 10 Gigabit Ethernet Port 4 x 10GbE SFP+ (Intel XL710-AM1) and 2 x 10GBASE-T (LAN-10G2T-X550) for each controller - PCIe Slot x8 (Gen3 x8): Pre-installed with a LAN-10G2T-X550 NIC (2 x 10GbE RJ45 ports), replaceable with a 40GbE NIC - PCIe Slot x4 (Gen2 x4): Pre-installed with a dual-port Mini-SAS adapter	call	
21	<a href="#">TS-h1683XU-RP-E2236-128G</a>	Intel® Xeon® E-2236 6-core 3.4 GHz processor (burst up to 4.8 GHz) - System Memory: 128 GB UDIMM DDR4 ECC (4 x 32GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay : 16 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ SmartNIC port, 2 x 10GBase-T port - USB 3.2 Gen 2 (10Gbps) Port: 2 x Type-C USB 3.2 Gen 2 10Gbps & 4 x Type-A USB 3.2 Gen 2 10Gbps	call	
22	<a href="#">TS-1683XU-RP-E2124-16G</a>	Intel® Xeon® E-2124 quad-core 3.3 GHz processor (burst up to 4.3 GHz) - System Memory 16 GB UDIMM DDR4 ECC (2 x 8GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 16 x 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps - 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps	call	
23	<a href="#">TS-EC1680U-E3-4GE-R2</a>	Intel® Xeon® E3-1245 v3 3.4 GHz Quad-core Processor, Total memory slots: 4 System memory: 4 GB DDR3 ECC RAM Memory module pre-installed: 2 GB x2 Memory expandable up to: 32 GB (8GB x4) , 16 x 3.5-inch SATA 6Gbps/3Gbps hard drive or 2.5-inch SATA, 6Gbps/3Gbps hard drive SSD hard drive, Built-in 2 x 10 GbE SFP+ ports (LAN-10G2SF-MLX) and 4 x GbE ports 40GbE is optional	call	
24	<a href="#">TS-1673U-RP-16G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (turbo core to 3.4 GHz) - System Memory 16 GB UDIMM DDR4 (2 x 8 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 16 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
25	<a href="#">TS-1673U-RP-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (turbo core to 3.4 GHz) - System Memory 16 GB UDIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 16 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
26	<a href="#">TS-1673AU-RP-16G</a>	AMD Ryzen™ Embedded V1500B quad-core 2.2 GHz processor - System Memory: 16 GB UDIMM DDR4 (1 x 16 GB) - Maximum Memory: 64 GB (2 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 16 x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/10M): 2 (also support 10M) - USB 3.2 Gen 2 (10Gbps) Port: 2 x Type-C & 1 x Type-A - HDMI Output: Optional via a PCIe graphics card	call	











27	<a href="#">TVS-1672XU-RP-i3-8G</a>	Intel® Core™ i3-8100 4-core 3.6 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 16 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps - 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps - HDMI Output 1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz)	call	
28	15-bay			
29	<a href="#">TVS-1582TU-i5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors Intel® HD Graphics 630 - System Memory 16GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512MB (DOM for dual OS) - Drive Bay 9 x 3.5-inch + 6 x 2.5-inch - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10G SFP+	call	
30	12-bay			
31	<a href="#">TS-1283XU-RP-E2124-8G</a>	Intel® Xeon® E-2124 quad-core 3.3 GHz processor (burst up to 4.3 GHz) - System Memory 8 GB UDIMM DDR4 ECC (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 12 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps	call	
32	<a href="#">TS-EC1280U-E3-4GE-R2</a>	Intel® Xeon® E3-1245 v3 quad-core 3.4 GHz processor, E3-1246 v3 quad-core 3.5 GHz processor or a compatible E3-1200 v3 family processor - System Memory 4GB UDIMM DDR3 ECC (2 x 2GB) - Flash Memory 512MB (DOM for dual OS) - Drive Bay 12 x 3.5-inch - mSATA slot 2 (mSATA flash module is optional) - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
33	<a href="#">TS-1277XU-RP-2600-8G</a>	AMD Ryzen™ 5 2600 6-core 3.4 GHz processor, Turbo Core 3.9 GHz - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 12 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - USB 3.0 port 4	call	
34	<a href="#">TS-1273AU-RP-8G</a>	AMD Ryzen™ Embedded V1500B quad-core 2.2 GHz processor - System Memory 8 GB UDIMM DDR4 (1 x 8 GB) - Maximum Memory 64 GB (2 x 32 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 2 (also support 10M) - USB 3.2 Gen 2 (10Gbps) Port: 2 x Type-C & 1 x Type-A - HDMI Output: Optional via a PCIe graphics card	call	
35	<a href="#">TS-1273U-RP-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - System Memory 8 GB UDIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 12 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
36	<a href="#">TVS-1272XU-RP-i3-4G</a>	Intel® Core™ i3-8100 4-core 3.6 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 4 GB UDIMM DDR4 (1 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 12 x 3.5-inch - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - Output HDMI 2.0 (up to 3840 x 2160 @ 60Hz)	call	
37	<a href="#">TS-1263XU-RP-4G</a>	AMD G-Series GX-420MC quad-core 2.0 GHz processor - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) V - Maximum Memory 16 GB (2 x 8 GB) - Drive Bay 12 x 2.5-inch or 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) - PCIe Slot 1 x PCIe Gen2 (x4)	call	
38	<a href="#">TS-1253BU-RP-4G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4 GB SODIMM DDR3L (2 x 2 GB) - Maximum Memory 8 GB (2 x 4GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 12 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - USB 3.0 port 4 - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe	call	
39	<a href="#">TS-1232PXU-RP-4G</a>	CPU AnnapurnaLabs Alpine AL324 64-bit ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory: 4 GB UDIMM DDR4 (1 x 4 GB) - Maximum Memory: 16 GB (1 x 16 GB) - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ - USB 3.2 Gen 1 port: 4	call	
40	<a href="#">TS-1232XU-RP-4G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 4 GB UDIMM DDR4 (1 x 4 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 12 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
41	9-bay			

42	<a href="#">TS-983XU-RP-E2124-8G</a>	Intel® Xeon® E-2124 quad-core 3.3 GHz processor (burst up to 4.3 GHz) - System Memory 8 GB UDIMM DDR4 ECC (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch + 5 x 2.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 1 x Gen3 x16 - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen1 5V/1A 5Gbps	call	
43	<a href="#">TS-977XU-RP-1200-4G</a>	AMD Ryzen™ 3 1200 4-core/4-thread 3.1 GHz processor, Turbo Core 3.4 GHz - System Memory 4 GB UDIMM DDR4 (1 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Drive Bay 4 x 3.5-inch + 5 x 2.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port 4 - USB 3.2 Gen 2 (10Gbps) Port 1 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps	call	
44	<a href="#">TVS-972XU-RP-i3-4G</a>	Intel® Core™ i3-8100 4-core 3.6 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 4 GB UDIMM DDR4 (1 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch + 5 x 2.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - USB 3.2 Gen 1 port 2	call	
45	8-bay			
46	<a href="#">TS-883XU-RP-E2124-8G</a>	Intel® Xeon® E-2124 quad-core 3.3 GHz processor (burst up to 4.3 GHz) - System Memory 8 GB UDIMM DDR4 ECC (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - USB 3.1 Gen 2 (10Gbps) Port 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps 4 x Type-A USB 3.1 Gen2 5V/1A 10Gbps	call	
47	<a href="#">TS-877XU-RP-2600-8G</a>	AMD Ryzen™ 5 2600 6-core 3.4 GHz processor, Turbo Core 3.9 GHz - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - USB 3.0 port 4	call	
48	<a href="#">TS-877XU-RP-1200-4G</a>	AMD Ryzen™ 3 1200 quad-core 3.1 GHz processor, Turbo Core 3.4 GHz - System Memory 4 GB UDIMM DDR4 (1 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4 - USB 3.0 port 4	call	
49	<a href="#">TS-873U-RP-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor, Turbo Core to 3.4 GHz - System Memory 8 GB UDIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
50	<a href="#">TS-873AU-RP-4G</a>	AMD Ryzen™ Embedded V1500B quad-core 2.2 GHz processor - System Memory: 4 GB UDIMM DDR4 (1 x 4 GB) - Maximum Memory: 64 GB (2 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: Optional via a network adapter - USB 3.2 Gen 2 (10Gbps) Port: 2 x Type-C, 1 x Type-A - HDMI Output: Optional via a PCIe graphics card	call	
51	<a href="#">TVS-872XU-RP-i3-4G</a>	Intel® Core™ i3-8100 4-core 3.6 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 4 GB UDIMM DDR4 (1 x 4GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ SmartNIC port - PCIe Slot 4	call	
52	<a href="#">TS-863XU-RP-4G</a>	AMD G-Series GX-420MC quad-core 2.0 GHz processor - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) - Maximum Memory 16 GB (2 x 8 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 2.5-inch or 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
53	<a href="#">TS-853BU-RP-4G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4GB DDR3L (2 x 2 GB) - Maximum Memory 8 GB (2 x 4GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
54	<a href="#">TS-853DU-RP-4G</a>	Intel® Celeron® J4125 quad-core 2.0 GHz processor (burst up to 2.7 GHz) - Graphic Processors : Intel® HD Graphics 600 - System Memory: 4 GB SO-DIMM DDR4 (1 x 4 GB) - Maximum Memory: 8 GB (2 x 4GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 2 (also support 10M) - USB 3.2 Gen 1 port: 2 - HDMI Output : 1, HDMI 1.4b	call	












55	<a href="#">TS-832XU-RP-4G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 4 GB UDIMM DDR4 (1 x 4 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
56	<a href="#">TS-832PXU-RP-4G</a>	CPU: AnnapurnaLabs Alpine AL324 64-bit ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory: 4 GB UDIMM DDR4 (1 x 4 GB) - Maximum Memory: 16 GB (1 x 16 GB) - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ - USB 3.2 Gen 1 port: 4	call	
57	4-bay			
58	<a href="#">TS-463XU-RP-4G</a>	AMD G-Series GX-420MC quad-core 2.0 GHz processor - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) - Maximum Memory 16 GB (2 x 8 GB) - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M)	call	
59	<a href="#">TS-453BU-RP-8G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4GB DDR3L (2 x 2 GB) - Maximum Memory 8 GB (2 x 4GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - USB 3.0 port 4 - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
60	<a href="#">TS-453BU-RP-4G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 8GB DDR3L (2 x 4 GB) - Maximum Memory 8 GB (2 x 4GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - USB 3.0 port 4 - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
61	<a href="#">TS-453DU-RP-4G</a>	Intel® Celeron® J4125 quad-core 2.0 GHz processor (burst up to 2.7 GHz) - Graphic Processors : Intel® HD Graphics 600 - System Memory: 4 GB SO-DIMM DDR4 (1 x 4 GB) - Maximum Memory: 8 GB (2 x 4GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 4 x 3.5-inch SATA 6Gb/s, 3Gb/s - USB 3.2 Gen 1 port2 - HDMI Output: 1, HDMI 1.4b	call	
62	<a href="#">TS-451Deu-2G</a>	Intel® Celeron® J4025 dual-core 2.0 GHz processor (burst up to 2.9 GHz) - Graphic Processors: Intel® HD Graphics 600 - System Memory: 2 GB SO-DIMM DDR4 (1 x 2 GB) - Maximum Memory: 8 GB (2 x 4GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 4 x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 2 (also support 10M) - USB 3.2 Gen 1 port: 2 -	call	
63	<a href="#">TS-432XU-RP-2G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 2 GB UDIMM DDR4 (1 x 2 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+	call	
64	<a href="#">TS-431XeU-2G</a>	CPU AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor - System Memory 2 GB SODIMM DDR3 (1 x 2 GB) - Maximum Memory 8 GB (1 x 8 GB) - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 4 x 3.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 1 x 10GbE SFP+	call	
65	<b>Expansion Unit</b>			
66	<a href="#">EJ1600-V2</a>	3U rackmount - Host Interface Three SAS (one input, one output, one reserved) 12Gbps for each controller, 4x port - Max. number of HDDs/SSDs supported 16 - Hard Drive Type 3.5" SAS12/6Gb/s, hard drive or 2.5" SAS SSD - Power Supply Unit Redundant/ Hot Swap ATX Power Supply, 450W, 90-240Vac~, 50-60Hz Support for hard disk's S.M.A.R.T. capacity RAID expansion enclosure LED identifier Location indication of RAID expansion enclosure Location indication of hard disks on RAID expansion enclosure Smart fan control In-band firmware update	call	










67	<a href="#">REXP-1620U-RP</a>	3U rackmount - Host Interface Three SAS 12Gbps 4x wide port - Max. number of HDDs/SSDs supported 16 - Hard Drive Type 3.5" SAS/SATA 12/6Gb/s, SAS/SATA 3Gb/s hard drive or 2.5" SAS/SATA SSD - Management via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. RAID expansion enclosure identifier 3. Locate RAID expansion enclosures 4. Locate hard disks on RAID expansion enclosure 5. Smart fan control by detecting system and hard drive temperature 6. In-band SAS firmware update	call	
68	<a href="#">REXP-1220U-RP</a>	2U rackmount - Host Interface Three SAS 12Gbps 4x wide port - Hard Drive Type 3.5" SAS/SATA 12/6Gb/s, SAS/SATA 3Gb/s hard drive or 2.5" SAS/SATA SSD - Managed via QNAP QTS OS 1. Supports disk S.M.A.R.T. information 2. RAID expansion enclosure identifier 3. Locate RAID expansion enclosures 4. Locate hard disks on RAID expansion enclosure 5. Smart fan control by detecting system and hard drive temperature 6. In-band SAS firmware update	call	
69	<a href="#">TL-R1200S-RP</a>	2U Rackmount - Drive Bay: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s - Host Interface: 3 x SFF-8088 - Hard Drive Type 3.5-inch SATA hard disk drives & 2.5-inch SATA hard disk drives & 2.5-inch SATA solid state drives	call	
70	<a href="#">TL-R400S</a>	1U Rackmount - Drive Bay: 4 x 3.5-inch SATA 6Gb/s, 3Gb/s - Host Interface: 1 x SFF-8088 - Drive Compatibility 3.5-inch SATA hard disk drives & 2.5-inch SATA hard disk drives & 2.5-inch SATA solid state drives	call	
71	<a href="#">TR-004U</a>	CPU Micro processor with hardware RAID - Drive Bay 4 x 2.5-inch or 3.5-inch SATA 3Gb/s - USB 3.2 Gen 1 port 1 x Type-C USB 3.2 Gen 1 (USB 3.2 Gen 1)	call	
72	<a href="#">TL-D1600S</a>	Drive Bay 12 x 3.5-inch SATA 6Gb/s, 3Gb/s + 4 x 2.5-inch SATA 6Gb/s, 3Gb/s - Host Interface 4 x SFF-8088 - Hard Drive Type: 3.5-inch SATA hard disk drives & 2.5-inch SATA hard disk drives & 2.5-inch SATA solid state drives	call	
73	<a href="#">TL-D400S</a>	Drive Bay 4 x 3.5-inch SATA 6Gb/s, 3Gb/s - Host Interface 1 x SFF-8088 - Hard Drive Type: 3.5-inch SATA hard disk drives & 2.5-inch SATA hard disk drives & 2.5-inch SATA solid state drives	call	
74	<a href="#">TR-004</a>	CPU Micro processor with hardware RAID - Drive Bay 4 x 2.5-inch or 3.5-inch SATA 3Gb/s - USB 3.0 port 1 x Type-C USB 3.0 (USB 3.1 Gen 1) -	call	
75	<a href="#">TR-002</a>	CPU Micro processor with hardware RAID - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - USB 3.2 Gen 2 (10Gbps) Port 1 x Type-C USB 3.2 Gen 2 10Gbps - Hard Drive Type: 3.5-inch SATA hard disk drives & 2.5-inch SATA hard disk drives & 2.5-inch SATA solid state drives	call	











77	<b>QWU-100</b>	CPU NXP Cortex-A7 900 MHz - System Memory 512MB - Flash Memory 4GB - Ethernet Port (RJ45) 2 (PoE x1) - Power Supply Unit USB type C, PoE port Notes: PoE needs to comply with IEEE 802.3af-15.4W standard - Power Consumption (W) 3.26 W	call	
78	<b>Tower Series</b>			
79	<b>28-bay</b>			
80	<a href="#">TS-2888X-W2123-32G</a>	Intel® Xeon® W-2123 4-core 3.6 GHz Processor (burst up to 3.9 GHz) - System Memory 32 GB RDIMM DDR4 ECC (4 x 8GB) - Maximum Memory 512 GB (8 x 64GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch + 20 x 2.5-inch - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GBASE-T - USB 2.0 port 4 - USB 3.2 Gen 1 port 6 -	call	
81	<b>16-bay</b>			
82	<a href="#">TVS-h1688X-W1250-32G</a>	Intel® Xeon® W-1250 6-core 3.3 GHz processor (boost up to 4.7 GHz) - Graphic Processors: Intel® UHD Graphics P630 - System Memory: 32GB ECC UDIMM DDR4 (2 x 16 GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 12 x 3.5-inch SATA 6Gb/s, 3Gb/s + 4 x 2.5-inch SATA 6Gb/s, 3Gb/s - Thunderbolt Port: Optional via the QXP-T32P 2-port Thunderbolt 3 PCIe adapter - USB 3.2 Gen 2 (10Gbps) Port 2 x Type-C & 4 x Type-A - HDMI Output 1, HDMI 1.4b (up to 4096 x 2160 @ 30Hz)	call	
83	<a href="#">TS-1685-D1521-16G</a>	Intel® Xeon® Processor D-1521, 4-core 2.4 GHz - System Memory 16GB non-ECC RAM (8GB UDIMM x 2) - Maximum Memory DDR4 128GB (with DDR4 32GB RDIMM x 4) - Flash Memory 512MB DOM - Drive Bay 12 x 2.5"/3.5" HDD/SSD slot 4 x 2.5" SSD slot, max 9.5mm drive height - Drive Compatibility SATA 6Gb/s HDD and SSD - M.2 SSD Slot 6 x M.2 2242/2260/2280/22110 SATA 6Gb/s SSD - Gigabit Ethernet Port 2 x 10GBASE-T ports, 4 x Gigabit ports - USB Port Front: 1 x USB 3.0 port; Rear: 2 x USB 3.0 port - Power Consumption (W) Sleep mode: 61.36 W In Operation: 127 W	call	
84	<a href="#">TS-1685-D1521-8G</a>	Intel® Xeon® D-1521 quad-core 2.4 GHz processor, Max turbo to 2.7 GHz - System Memory 8GB UDIMM DDR4 (1 x 8GB) - Maximum Memory UDIMM: 64 GB (4 x 16 GB) RDIMM: 128GB (4 x 32 GB) - Flash Memory 512MB (DOM for dual OS) - Drive Bay 12 x 3.5-inch + 4 x 2.5-inch - M.2 SSD Slot 6 x M.2 22110/2280/2260/2242 SATA 6Gb/s slot - 10 Gigabit Ethernet Port 2 x 10GBASE-T	call	
85	<a href="#">TS-1677X-1600-8G</a>	AMD Ryzen™ 5 1600 6-core/12-thread 3.2 GHz processor (Turbo Core to 3.6 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 8 GB UDIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 12 x 2.5-inch or 3.5-inch + 4 x 2.5-inch - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GBASE-T (10G/5G/2.5G/1G/100M)	call	
86	<b>12-bay</b>			
87	<a href="#">TVS-1282T3-i5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors Intel® HD Graphics 630 - System Memory 16GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512MB (DOM for dual OS) - Drive Bay 8 x 3.5-inch + 4 x 2.5-inch - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 2 x 10GBASE-T	call	
88	<a href="#">TVS-1282T-i5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors Intel® HD Graphics 630 - System Memory 16 GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB - Flash Memory 512MB (DOM for dual OS) - Drive Bay 8x 2.5"/3.5" SATA 6Gb/s, 4x 2.5" SATA 6Gb/s - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port 6 x 10GBASE-T - Thunderbolt™ 2 Thunderbolt™ 2 high-speed port	call	
89	<a href="#">TVS-1282-i5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors Intel® HD Graphics 630 - System Memory 16 GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB - Flash Memory 512MB (DOM for dual OS) - Drive Bay 8 x 3.5-inch + 4 x 2.5-inch - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 -	call	
90	<b>9-bay</b>			











91	<a href="#">TS-963X-2G</a>	AMD G-Series GX-420MC quad-core 2.0 GHz processor - System Memory 2 GB SO-DIMM DDR3/DDR3L - Maximum Memory 16 GB (2 x 8 GB) - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 5 x 2.5-inch or 3.5-inch + 4 x 2.5-inch - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) - USB 3.0 port 2	call	
92	<a href="#">TVS-951X-2G</a>	Intel® Celeron® 3865U dual-core 1.8 GHz processor - Graphic Processors Intel® HD Graphics 610 - System Memory 2 GB SO-DIMM DDR4 (1 x 2 GB) - Maximum Memory 32 GB (2 x 16 GB) - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 5 x 2.5-inch or 3.5-inch + 4 x 2.5-inch - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) - USB 3.0 port 4	call	
93	<a href="#">TS-932X-8G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 8 GB SODIMM DDR4 (1x 8 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 5x 3.5-inch+ 4 x 2.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10G SFP+	call	
94	<a href="#">TS-932X-2G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 2 GB SODIMM DDR4 (1x 2 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 5x 3.5-inch+ 4 x 2.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10G SFP+	call	
95	8-bay			
96	<a href="#">TS-h886-D1622-16G</a>	Intel® Xeon® D-1622 quad-core 2.6 GHz processor (burst up to 3.2 GHz) - System Memory: 16 GB UDIMM DDR4 ECC (2 x 8 GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory: 5GB (Dual boot OS protection) - Drive Bay: 6 x 3.5-inch SATA 6Gb/s, 3Gb/s + 2 x 2.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 4 (also support 10M) - USB 3.2 Gen 1 port : 3	call	
97	<a href="#">TVS-882-I5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors Intel® HD Graphics 630 - System Memory 16 GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB - Flash Memory 512MB (DOM for dual OS) - Drive Bay 6 x 3.5-inch + 2 x 2.5-inch - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4	call	
98	<a href="#">TVS-882-i3-8G</a>	Intel® Core™ i3-7100 dual-core 3.9 GHz processor - Graphic Processors Intel® HD Graphics 630 - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB - Flash Memory 512MB (DOM for dual OS) - Drive Bay 6 x 3.5-inch + 2 x 2.5-inch - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4	call	
99	<a href="#">TVS-882BR-ODD-i5-16G</a>	Intel® Core™ i5-7500 quad-core 3.4 GHz processor, Max turbo to 3.8 GHz - Graphic Processors 9th-generation Intel® HD Graphics - System Memory 16GB UDIMM DDR4 (2 x 8GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512MB (DOM for dual OS) - Drive Bay 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - 5.25-inch Expansion Bay 1 x 5.25" disc burner or 2 x slim SATA disc burners *pre-installed with a Blu-ray ODD - Pre-installed in 5.25-inch Expansion Bay LG WH16NS58D - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - USB 3.2 Gen 1 port 5 - HDMI Output 3, HDMI 1.4b	call	
100	<a href="#">TVS-872N-i3-8G</a>	Intel® Core™ i3-8100T 4-core 3.1 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 8 GB SODIMM DDR4 (2 x 4 GB) - Maximum Memory 32 GB ( 2 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot 2 x M.2 2280 PCIe Gen3 x2 slots - Gigabit Ethernet Port (RJ45) 2 - 5 Gigabit Ethernet Port 1 x 5GbE(5G/2.5G/1G/100M) - USB 3.2 Gen 1 port 1 - USB 3.2 Gen 2 (10Gbps) Port 2 x Type-C USB 3.2 Gen 2 5V/3A 10Gbps - 2 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps	call	
101	<a href="#">TS-877-1600-8G</a>	AMD Ryzen™ 5 1600 6-core/12-thread 3.2 GHz processor (Turbo Core to 3.6 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 8 GB UDIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 6 x 2.5-inch or 3.5-inch + 2 x 2.5-inch - M.2 SSD Slot 2 x M.2 22110/2280/2260/2242 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	


















102	<a href="#">TVS-873e-8G</a>	AMD R-Series RX-421BD quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Embedded Radeon™ R7 Graphics Processor - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	
103	<a href="#">TS-873-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - 10 Gigabit Ethernet Port Optional via a PCIe adapter - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
104	<a href="#">TS-832X-8G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 8 GB SODIMM DDR4(1 x 8 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ - USB 3.0 port 3 - Audio Output 1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)	call	
105	<a href="#">TS-832PX-4G</a>	CPU AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory: 4 GB SODIMM DDR4(1 x 4 GB) - Maximum Memory: 16 GB (1 x 16 GB) - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 2 x 10GbE SFP+ - USB 3.2 Gen 1 port: 3	call	
106	<a href="#">TS-832X-2G</a>	CPU AnnapurnaLabs Alpine AL-324 ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 2 GB SODIMM DDR4(1 x 2 GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 8 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 2 x 10GbE SFP+ - USB 3.0 port 3 - Audio Output 1 x built-in speaker, 1 x 3.5mm line out jack (for amplifiers or speakers)	call	
107	6-bay			
108	<a href="#">TS-h686-D1602-8G</a>	Intel® Xeon® D-1602 dual-core 2.5 GHz processor (burst up to 3.2 GHz) - System Memory: 8 GB UDIMM DDR4 ECC (2 x 4 GB) - Maximum Memory: 128 GB (4 x 32 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay: 4 x 3.5-inch SATA 6Gb/s, 3Gb/s + 2 x 2.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot : 2 x M.2 22110/2280 NVMe PCIe Gen3 x4 slots - 2.5 Gigabit Ethernet Port (2.5G/1G/100M) : 4 (also support 10M) - USB 3.2 Gen 1 port: 3	call	
109	<a href="#">TVS-682-I3-8G</a>	Intel® Core™ i3-7100 dual-core 3.9 GHz processor - Graphic Processors Intel® HD Graphics 630 - System Memory 8 GB UDIMM DDR4 (2 x 4GB) - Maximum Memory 64 GB - Flash Memory 512MB (DOM for dual OS) - Drive Bay 4 x 3.5-inch + 2 x 2.5-inch - M.2 SSD Slot 2 x M.2 2242/2260/2280/22110 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4	call	
110	<a href="#">TVS-672N-I3-4G</a>	Intel® Core™ i3-8100T 4-core 3.1 GHz Processor - Graphic Processors Intel® UHD Graphics 630 - System Memory 4 GB SODIMM DDR4 (2 x 2 GB) - Maximum Memory 32 GB (2 x 16 GB) - Flash Memory 5GB (Dual boot OS protection) - Drive Bay 6 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot 2 x M.2 2280 PCIe Gen3 x2 slots - Gigabit Ethernet Port (RJ45) 2 - 5 Gigabit Ethernet Port 1 x 5GbE(5G/2.5G/1G/100M) - USB 3.2 Gen 1 port 1 - USB 3.2 Gen 2 (10Gbps) Port 2 x Type-C USB 3.2 Gen 2 5V/3A 10Gbps - 2 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps	call	
111	<a href="#">TVS-673e-8G</a>	CPU AMD R-Series RX-421BD quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Embedded Radeon™ R7 Graphics Processor - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 6 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter - USB 3.0 port 4 - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
112	<a href="#">TVS-673e-4G</a>	CPU AMD R-Series RX-421BD quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Embedded Radeon™ R7 Graphics Processor - System Memory 4 GB SO-DIMM DDR4 (2 x 2 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 6 x 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter - USB 3.0 port 4 - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
113	<a href="#">TS-673-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 4 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 6 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	

114	<a href="#">TS-673-4G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 4 GB SO-DIMM DDR4 (2 x 2 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 6 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	
115	4-bay			
116	<a href="#">TVS-473e-8G</a>	AMD R-Series RX-421BD quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Embedded Radeon™ R7 Graphics Processor - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch - 10 Gigabit Ethernet Port Optional via a PCIe adapter - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
117	<a href="#">TVS-473e-4G</a>	AMD R-Series RX-421BD quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Embedded Radeon™ R7 Graphics Processor - System Memory 8 GB SO-DIMM DDR4 (2 x 2 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch - 10 Gigabit Ethernet Port Optional via a PCIe adapter - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe adapter	call	
118	<a href="#">TS-473-8G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	
119	<a href="#">TS-473-4G</a>	AMD R-Series RX-421ND quad-core 2.1 GHz processor (Turbo Core to 3.4 GHz) - Graphic Processors Optional via a PCIe adapter - System Memory 4 GB SO-DIMM DDR4 (2 x 2 GB) - Maximum Memory 64 GB (4 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch - M.2 SSD Slot 2 x M.2 2280/2260 SATA 6Gb/s slots - Gigabit Ethernet Port (RJ45) 4 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	
120	<a href="#">TS-453D-4G</a>	Intel® Celeron® J4125 quad-core 2.0 GHz processor (burst up to 2.7 GHz) - Graphic Processors: Intel® HD Graphics 600 - System Memory: 4 GB SO-DIMM DDR4 (1 x 4 GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 4 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: Optional via PCIe expansion card - USB 3.2 Gen 1 port: 2 - HDMI Output : 1, HDMI 2.0 (up to 4096 x 2160 @ 60Hz)	call	
121	<a href="#">TS-453Be-4G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port Optional via a PCIe adapter	call	
122	<a href="#">HS-453DX-8G</a>	Intel® Celeron® J4105 quad-core 1.5 GHz processor (burst up to 2.5 GHz) - Graphic Processors Intel® HD Graphics 600 - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot 2 x M.2 2280 SATA 6Gb/s slots - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M)	call	
123	<a href="#">TBS-453DX-8G</a>	Intel® Celeron® J4105 quad-core 1.5 GHz processor (burst up to 2.5 GHz) - Graphic Processors Intel® HD Graphics 600 - System Memory 8 GB SO-DIMM DDR4 (2 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - M.2 SSD Slot 4 x M.2 2280 SATA 6Gb/s slots - 10 Gigabit Ethernet Port 1 x 10GBASE-T (10G/5G/2.5G/1G/100M)	call	

124	<a href="#">TS-451+-2G</a>	Intel® Celeron® J1900 quad-core 2.0 GHz processor (burst up to 2.42 GHz) - Graphic Processors Intel® HD Graphics - System Memory 2 GB SO-DIMM DDR3L (1 x 2 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 4 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45) 2	call	
125	<a href="#">TS-431X3-4G</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL314, 4-core, 1.7GHz - System Memory: 4 GB SODIMM DDR3 (1 x 4 GB) - Maximum Memory: 8 GB (1 x 8 GB) - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 4x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 1 x 10GbE SFP+ - USB 3.2 Gen 1: 3	call	
126	<a href="#">TS-431X2-2G</a>	CPU AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor - System Memory 2 GB SODIMM DDR3 RAM - Maximum Memory 8 - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5"/3.5" SATA 6Gb/s - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 1 x 10G SFP+	call	
127	<a href="#">TS-431X-2G</a>	CPU Annapurna Labs Alpine AL-212 2-core 1.7 GHz - System Memory 2 GB SODIMM DDR3 (1 x 2 GB) - Maximum Memory 8 GB (1 x 8 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4x 3.5-inch - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port 1 x 10GbE SFP+	call	
128	<a href="#">TS-431P3-2G</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL314, 4-core, 1.7GHz - System Memory: 2GB SO-DIMM DDR3 - Maximum Memory: 8GB DDR3 - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 4x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 1 - USB 3.2 Gen 1 port: 3	call	
129	<a href="#">TS-431P2-1G</a>	CPU AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor - System Memory 1 GB SODIMM DDR3L RAM - Maximum Memory 8 GB - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4 x 2.5"/3.5" SATA 6Gb/s - Gigabit Ethernet Port (RJ45) 2	call	
130	<a href="#">TS-431P3-4G</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL-212, 2-core, 1.7GHz - System Memory 1GB DDR3 - Maximum Memory 1GB DDR3 - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 4x 3.5-inch - Gigabit Ethernet Port (RJ45) 2	call	
131	<a href="#">TS-431KX-2G</a>	CPU: AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz - System Memory: 2 GB SODIMM DDR3 (1 x 2 GB) - Maximum Memory: 8 GB (1 x 8 GB) - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 4x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: 1 x 10GbE SFP+ - USB 3.2 Gen 1 port3	call	
132	<a href="#">TS-431K</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz - System Memory: 1GB DDR3 - Maximum Memory 1GB DDR3 - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 4x 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45): 2 - USB 3.2 Gen 1 port: 3	call	
133	3-bay			
134	<a href="#">TS-351-4G</a>	Intel® Celeron® J1800 dual-core 2.41 GHz processor (burst up to 2.58 GHz) - Graphic Processors Intel® HD Graphics - System Memory 4 GB SODIMM DDR3L (1 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Drive Bay 3 x 3.5-inch - M.2 SSD Slot 2 x M.2 2280 NVMe 500 MB/s slots - SD Cache Acceleration Support Drive bay 3 M.2 Slots 1 to 2 - HDMI Output 1, HDMI 1.4a (up to 1080p)	call	

135	<a href="#">TS-351-2G</a>	Intel® Celeron® J1800 dual-core 2.41 GHz processor (burst up to 2.58 GHz) - Graphic Processors Intel® HD Graphics - System Memory 2 GB SODIMM DDR3L (1 x 2 GB) - Maximum Memory 8 GB (2 x 4 GB) - Drive Bay 3 x 3.5-inch - M.2 SSD Slot 2 x M.2 2280 NVMe 500 MB/s slots - SD Cache Acceleration Support Drive bay 3 M.2 Slots 1 to 2 - HDMI Output 1, HDMI 1.4a (up to 1080p)	call	
136	<a href="#">TS-332X-4G</a>	CPU AnnapurnaLabs Alpine AL-324 64-bit ARM® Cortex-A57 quad-core 1.7GHz processor - System Memory 4 GB SODIMM DDR4 (1 x 2GB) - Maximum Memory 16 GB (1 x 16 GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 3 x 3.5-inch - M.2 SSD Slot 3 x M.2 2280 SATA 6Gb/s slots - 10 Gigabit Ethernet Port 1 x 10GbE SFP+	call	
137	<a href="#">TS-328</a>	CPU Realtek RTD 1296 ARM® Cortex-A53 quad-core 1.4 GHz processor - System Memory 2 GB DDR4 RAM, not expandable - Flash Memory 4 GB (Dual boot OS protection) - Drive Bay 3 x 3.5-inch - Gigabit Ethernet Port (RJ45) 2	call	
138	2-bay			
139	<a href="#">TS-253D-4G</a>	Intel® Celeron® J4125 quad-core 2.0 GHz processor (burst up to 2.7 GHz) - Graphic Processors : Intel® HD Graphics 600 - System Memory: 4 GB SO-DIMM DDR4 (1 x 4 GB) - Maximum Memory: 8 GB (2 x 4GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: Optional via PCIe expansion card - USB 3.2 Gen 1 port: 2	call	
140	<a href="#">TS-253Be-4G</a>	Intel® Celeron® J3455 quad-core 1.5 GHz processor (burst up to 2.3 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - Gigabit Ethernet Port (RJ45) 2 - 10 Gigabit Ethernet Port Optional via PCIe expansion card	call	
141	<a href="#">TS-251B-4G</a>	Intel® Celeron® J3355 dual-core 2.0 GHz processor (burst up to 2.5 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 4 GB SO-DIMM DDR3L (1 x 4 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - 10 Gigabit Ethernet Port Optional via PCIe expansion card - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe expansion card	call	
142	<a href="#">TS-251B-2G</a>	Intel® Celeron® J3355 dual-core 2.0 GHz processor (burst up to 2.5 GHz) - Graphic Processors Intel® HD Graphics 500 - System Memory 2 GB SO-DIMM DDR3L (1 x 2 GB) - Maximum Memory 8 GB (2 x 4 GB) - Flash Memory 4GB (Dual boot OS protection) - Drive Bay 2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - M.2 SSD Slot Optional via a PCIe adapter - 10 Gigabit Ethernet Port Optional via PCIe expansion card - USB 3.1 Gen 2 (10Gbps) Port Optional via a PCIe expansion card	call	
143	<a href="#">TS-251+2G</a>	Intel® Celeron® J1900 quad-core 2.0 GHz processor (burst up to 2.42 GHz) - Graphic Processors Intel® HD Graphics - System Memory 2 GB SO-DIMM DDR3L (1 x 2 GB) - Maximum Memory 8 GB - Flash Memory 512MB (Dual boot OS protection) - Drive Bay 2 x 2.5-inch or 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45) 2	call	
144	<a href="#">TS-251D-2G</a>	Intel® Celeron® J4025/J4005 dual-core 2.0 GHz processor - Graphic Processors : Intel® HD Graphics 600 - System Memory: 2 GB SO-DIMM DDR4 (1 x 2 GB) - Maximum Memory: 8 GB (2 x 4GB) - Flash Memory: 4GB (Dual boot OS protection) - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - 10 Gigabit Ethernet Port: Expandable with an optional PCIe adapter - USB 3.2 Gen 1 port: 2	call	
145	<a href="#">TS-251+8G</a>	Intel® Celeron® 2.41GHz dual-core processor (burst up to 2.58GHz) - DRAM 1GB DDR3L RAM - Flash Memory 512MB DOM - Hard Disk Drive 2 x 3.5" or 2.5" SATA 6Gb/s, SATA 3Gb/s hard drive or SSD - LAN Port 2 x Gigabit RJ-45 Ethernet port	call	

146	<a href="#">TS-231P3-2G</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL314, 4-core, 1.7GHz - System Memory: 2GB SO-DIMM DDR3 - Maximum Memory: 8GB DDR3 - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - 2.5 Gigabit Ethernet Port (2.5G/1G/100M): 1 - USB 3.2 Gen 1 port: 3	call	
147	<a href="#">TS-231P2-1G</a>	CPU AnnapurnaLabs Alpine AL-314 32-bit ARM® Cortex-A15 quad-core 1.7GHz processor - System Memory 1 GB SODIMM DDR3L RAM - Maximum Memory 8 GB (1 x 8GB) - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 2 x 3.5-inch - Gigabit Ethernet Port (RJ45) 2	call	
148	<a href="#">TS-231P3-4G</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL-212, 2-core, 1.7GHz - System Memory 1GB DDR3 - Maximum Memory 1GB DDR3 - Flash Memory 512 MB (Dual boot OS protection) - Drive Bay 2x 3.5-inch - Gigabit Ethernet Port (RJ45) 2 - USB 3.0 port 3	call	
149	<a href="#">TS-231K</a>	CPU AnnapurnaLabs, an Amazon company Alpine AL214, 4-core, 1.7GHz - System Memory: 1GB DDR3 - Maximum Memory 1GB DDR3 - Flash Memory: 512 MB (Dual boot OS protection) - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45): 2 - USB 3.2 Gen 1 port: 3	call	
150	<a href="#">TS-230</a>	CPU Realtek RTD1296 quad-core 1.4GHz processor - System Memory: 2 GB DDR4, not expandable - Flash Memory: 4 GB (Dual boot OS protection) - Drive Bay: 2 x 3.5-inch SATA 6Gb/s, 3Gb/s - Gigabit Ethernet Port (RJ45): 1 - USB 3.2 Gen 1 port: 2	call	
151	<a href="#">TS-228A</a>	CPU Realtek RTD1295 quad-core 1.4GHz processor - System Memory 1 GB DDR4, not expandable - Flash Memory 4 GB (Dual boot OS protection) - Drive Bay 2 x 3.5-inch - Gigabit Ethernet Port (RJ45) 1	call	
152	<b>1-bay</b>			
153	<a href="#">TS-128A</a>	CPU Realtek RTD1295 quad-core 1.4GHz processor - System Memory 1 GB DDR4, not expandable - Flash Memory 4 GB (Dual boot OS protection) - Drive Bay 1 x 3.5 inch SATA 6Gbps - Gigabit Ethernet Port (RJ45) 1	call	
154	<b>License</b>			
155	<b>NAS Channel</b>			
156	<b>LIC-CAM-NAS-1CH</b>	1 IP camera license activation key for Surveillance Station	call	
157	<b>LIC-CAM-NAS-2CH</b>	2 IP camera license activation keys for Surveillance Station	call	
158	<b>LIC-CAM-NAS-4CH</b>	4 IP camera license activation keys for Surveillance Station	call	
159	<b>QVR Pro</b>			
160	<b>LIC-SW-QVRPRO-GOLD-EI</b>	QVR Pro Gold App Including 8 IP camera license activation key for QVR Pro	call	
161	<b>LIC-SW-QVRPRO-1CH-EI</b>	1 IP camera license activation key for QVR Pro	call	
162	<b>LIC-SW-QVRPRO-4CH-EI</b>	4 IP camera license activation key for QVR Pro	call	
163	<b>LIC-SW-QVRPRO-8CH-EI</b>	8 IP camera license activation key for QVR Pro	call	
164	<b>Anti Virus</b>			
165	<b>LIC-SW-MCAFEE-3Y-EI</b>	3 Years	call	
166	<b>LIC-SW-MCAFEE-2Y-EI</b>	2 Years	call	

167	LIC-SW-MCAFEE-1Y-EI	1 Year	call	
168				
169	Rail			
170	Rail-A02-90	Rail Kit for TS-EC2480U-RP rackmount models	call	
171	Rail-A03-57	Rail Kit for 2U/3U rackmount models	call	
172	Rail-B02	Rail kit for Rackmount NAS Models	call	
173	Rail-B01	Rail kit for 2U rackmount models: TVS-x71U, TS-x53U, x70U, x69U	call	
174	Rail-C01	Rail kit for 1U rackmount models. Complies with ANSI/EIA-RS-310-D.	call	

D.D.C PERSIA

TelFax : 98 21 88 54 18 00

98 21 88 55 55 58

98 21 88 10 20 01 - 5

[www.ddcpersia.com](http://www.ddcpersia.com)

[info@ddcpersia.com](mailto:info@ddcpersia.com)