













www.ddcpersia.com

























لیست قیمت

شماره تماس: ۰۲۱-۵۴۸۷۱۰۰۰








































DAHUA - camera,nvr						
Items	Description	User Price				
CVI		User Price (با گارانتی پارس ارتباط)	با گارانتی الماس ایرانیان USER PRICE	گارانتی فراگستر		
1	DH-HAC-HFW1500THP-I8-0360B	5MP HDCVI IR Bullet Camera, 1/2.7" Progressive Scan CMOS 20fps@5MP, 25/30fps@4MP (16:9 video output) 3.6mm fixed lens, Aperture: F1.85 DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Support Electronic Defog, HD/SD switchable Max IR length 80m, Smart IR, IP67, DC12V/20	IRR 18,860,000	IRR 15,600,000		
2	DH-HAC-HDW1500TRQP-A	5MP Starlight HDCVI Quick-to-install IR Eyeball Camera * The parameters and datasheets below can only be applied to 1500-S2 series. * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. > Max 25 fps@5MP (16:9 video output) > Quick-to-install eyeball saves installation time CVI/CVBS/AHD/TVI switchable	IRR 14,280,000	IRR 14,500,000	IRR 13,000,000	
3	DH-HAC-HDW1500TLMQP-0280B-S2	5MP Starlight HDCVI Quick-to-install IR Eyeball Camera* The parameters and datasheets below can only be applied to 1500-S2 series. * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. > Max 25 fps@5MP (16:9 video output)> Quick-to-install eyeball saves installation time > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)	IRR 15,220,000			
4	DH-HAC-HFW1500TP-0280B-S2	Max. 20fps@5MP · Built-in mic · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V		IRR 14,800,000		
5	DH-HAC-HFW1500TP-0360B-S2	5MP HDCVI IR Bullet Camera. Max. 20fps@5MP · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V	IRR 15,060,000			
6	DH-HAC-HFW1500TP-A-S2-0360B	The parameters and datasheets below can only be applied to 1500-S2 series. · Max 25fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens (2.8 mm optional) · Built-in mic(-A) · Max. IR length 30 m, Smart IR	IRR 15,610,000			
7	DH-HAC-HFW1500DP(S)	5Megapixel 1/2.7" CMOS 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P 3.6mm fixed lens & 6mm Fixed Lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable Supports OSD Menu Max. IR length 80m, Smart IR IP67, DC12V	IRR 21,010,000	IRR 21,600,000		
8	DH-HAC-HDW1500TQP-A(S)	Max 25 fps@5MP (16:9 video output) · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 3.6 mm fixed lens (2.8 mm, 6 mm optional) · Built-in mic(-A) · Max. IR length 40 m, Smart IR				
9	DH-HAC-HFW1500SLP	1/2.7" Progressive CMOS · HD and SD output switchable · Day/Night (ICR), BLC / HLC / DWDR / AGC · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR IP67, DC12 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P				
10	DH-HAC-HFW1500RP-Z-IRE6	Max. 20fps@5MP(2592x1944). 1/2.7" Progressive CMOS · 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P · HD and SD output switchable · Built-in mic · 2.7-12mm motorized lens · IP67, DC12V · Max. IR length 60m, Smart IR	IRR 30,150,000			
11	DH-HAC-HFW1500CMP	HAC-HFW1500CM-A-POC 5MP Starlight HDCVI POC IR Bullet Camera * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version. >The parameters and datasheets below can only be applied to 1500-S2 series.> Max 25 fps@5MP (16:9 video output)> CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm optional)> Max. IR length 30m, Smart IR · Built-in	IRR 16,650,000			
12	DH-HAC-HFW1500TLP	HAC-HFW1500TL 5MP Starlight HDCVI IR Bullet Camera * The parameters and datasheets below can only be applied to 1500-S2 series * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version.> Max 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable> 3.6 mm fixed lens (2.8 mm, 6 mm optional)	IRR 15,870,000			












13	DH-HAC-HFW1400DP-S3-0360B	1/3" 4.1 Megapixel CMOS 25/30fps@4MP, 25/30fps@1080P, 25/30fps@720P 3.6mm fixed lens, HD and SD output switchable DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR OSD Menu, Max. IR length 80m, Smart IR, IP67, DC12V	IRR 17,260,000			
14	DH-HAC-HFW1400TP-A	4MP HDCVI IR Bullet Camera - Max. 30fps@4MP - Built-in mic - IP67, DC12V, - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional), - Max. IR length 30m, Smart IR				
15	DH-HAC-HFW1400SP	Max 30fps@4MP(2560x1440) - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 30m, Smart IR - IP67, DC12V				
16	DH-HAC-HFW1400TP(S)	Max. 30fps@4MP - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 30m, Smart IR - IP67, DC12V				
17	DH-HAC-HFW1400CMP	4MP HDCVI IR Bullet Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP, 3.6mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR	IRR 12,820,000			
18	DH-HAC-HFW1400RP(S)	Megapixel camera with 1/3" CMOS sensor and HD-CVI (High Definition Composite Video Interface), length 20m, Smart IR-D-WDR - Wide Dynamic Range 2D-DNR - Digital Noise Reduction.BLC/HLC - Back Light / High Light Compensation ICR - Movable InfraRed filter.Sharpness - sharper image outlines AGC - Automatic Gain Control.Privacy zones.Mirror - Mirror image				
19	DH-HAC-HDW1400TRQP-A-0280B-S3	4MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP, 2.8mm fixed lens, Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR	IRR 9,620,000			
20	DH-HAC-HDW1400MP	4MP HDCVI IR Eyeball Camera - Max 30fps@4MP - IP67, DC12V - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 30m, Smart IR				
21	DH-HAC-HDW1400EMP-A	- Max. 30fps@4MP(2560x1440) - Built-in mic - IP67, DC12V - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 50m, Smart IR				
22	DH-HAC-HDW1409TP-A-LED	4MP Full-color Starlight HDCVI Eyeball Camera - Full-color starlight - 40 m LED distance, - Max. 30fps@4MP - CVI/CVBS/AHD/TVI switchable, - Built-in mic (-A) - 3.6 mm fixed lens (2.8 mm optional) - IP67, 12V±30% DC				
23	DH-HAC-HDW1400TP-Z-A	- Max 30fps@4MP(2560x1440) - HD and SD output switchable - Built-in mic - IP67, DC12V - 2.7-12mm motorized lens - Max. IR length 60m, Smart IR				
24	DH-HAC-HDW1400TRQP-0280B-S3	4MP HDCVI Quick-to-install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@4MP 2.8mm fixed lens CVI/TVI/AHD/CVBS Switchable, Support OSD Menu DWDR/E-Defog/BLC/HLC/AWB/AGC/2D DNR/Day-Night Auto ICR	IRR 8,070,000			
25	2MP FIX LENS		P			
26	DH-HAC-HFW1230DP(S)	1/2.8" 2.1Megapixel CMOS (Starlight)25/30fps@1080P, 25/30/50/60fps@720P3.6mm Fixed lensDWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 3DNRHD and SD output switchableOSD MenuMax. IR length 80m, Smart IRIP67, DC12V				
27	DH-HAC-HDW1500EMP-A	- Max. 20fps@5MP(2592x1944) - Built-in mic - IP67, DC12V - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 50m, Smart IR				
28	DH-HAC-HDW1509TLP-A-LED	5MP Full-color Starlight HDCVI Eyeball Camera - Full-color starlight - 20 m LED distance, - Max. 20fps@5MP - CVI/CVBS/AHD/TVI switchable, - Built-in mic (-A) - 3.6 mm fixed lens (2.8 mm optional) - IP67, 12V±30% DC	IRR 19,610,000			
29	DH-HAC-HFW1509TLMP-A-LED	5MP Full-color HDCVI Bullet Camera -> Max 25 fps@5MP (16:9 video output) > 120 dB true WDR, 3D NR 24/7 color imaging > 40 m illumination distance> CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional)> IP67, 12	IRR 21,420,000			
30	DH-HAC-HFW1509TLMP-LED	- Full-color starlight - 40 m LED distance - Max. 20fps@5MP - CVI/CVBS/AHD/TVI switchable - Built-in mic (-A) - 3.6 mm fixed lens	IRR 19,820,000	IRR 20,700,000		
31	HAC-HDW1509TLQP-LED-0280B	5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output)> 120dB true WDR, 3D NR > 24/7 color imaging> 20 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional) > IP67, 12 V DC	IRR 22,200,000	IRR 20,300,000		
32	HAC-HDW1509TLQP-A-LED	5MP Full-color HDCVI Quick-to-install Eyeball Camera > Max 25 fps@5MP (16:9 video output)> 120dB true WDR, 3D NR > 24/7 color imaging> 20 m illumination distance > CVI/CVBS/AHD/TVI switchable > Built-in mic (-A)> 3.6 mm fixed lens (2.8 mm optional) > IP67, 12 V DC	IRR 21,420,000			
33	DH-HAC-HDW1500TP-Z-A	- Max. 20fps@5MP(2592x1944), 1/2.7"Progressive CMOS - 20fps@5MP, 25/30fps@4MP, 25/30fps@1080P - HD and SD output switchable- Built-in mic - 2.7-12mm motorized lens - IP67, DC12V - Max. IR length 60m, Smart IR				
34	DH-HAC-HFW1200RP	- 2MP HDCVI IR Bullet Camera - Max 30fps@1080P(1920x1080) - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 20m, Smart IR - IP67, DC12V				
35	DH-HAC-HDW1230TLP-A	- 2MP Starlight HDCVI IR Eyeball Camera - Max. 30fps@1080P - HD and SD output switchable - 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR length 40m, Smart IR - IP67, DC12V, Built in Mic				

36	DH-HAC-HDW1230EMP-A	<ul style="list-style-type: none"> · 2MP Starlight HDCVI IR Eyeball Camera · Max. 30fps@1080P · HD and SD output switchable, - Built-in mic · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR · IP67, DC12V 				
37	DH-HAC-HDW1239TP-A-LED-0280B-S2	<ul style="list-style-type: none"> · Full-color starlight · 40m LED distance · Max. 30fps@1080P · CVI/CVBS/AHD/TVI switchable · 3.6mm fixed lens (2.8mm Optional) · IP67, 12V±30% DC 	IRR 16,830,000			
38	HAC-HFW1231TMP-I8-A(S)	2MP HDCVI IR Bullet Camera-> Max 30 fps@1080P 2MP Starlight HDCVI IR Bullet Camera > 3.6 mm fixed lens (2.8 mm, 6 mm optional)Day/Night Auto switch by ICR BLC BLC/WDR/HLC-WDR 130 dBIP67, DC 12 V				
39	DH-HAC-HFW1209TLMP-LED-0360B	<ul style="list-style-type: none"> 2MP Full-color HDCVI Bullet Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 3.6mm Fixed lens Min. Illumination 0.001 Lux/F1.6, 30IRE, 0 Lux LED on WDR(120dB), Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR 5MP HDCVI Active Deterrence Camera > Max 20fps@5MP > HD and SD output switchable > 2.8mm fixed lens (3.6mm optional), > Max. IR length 20m, Smart IR > Built-in PIR, 14±1m/110°detecting range/angle > Active deterrence with white light & siren > IP67, DC12V 	IRR 11,710,000			
40	DH-HAC-ME1500CP	<ul style="list-style-type: none"> · 2MP HDCVI Active Deterrence Camera > Max 20fps@5MP > HD and SD output switchable > 2.8mm fixed lens (3.6mm optional), > Max. IR length 20m, Smart IR > Built-in PIR, 14±1m/110°detecting range/angle > Active deterrence with white light & siren > IP67, DC12V 				
41	DH-HAC-ME1200EP-LED	<ul style="list-style-type: none"> · 2MP HDCVI Active Deterrence Camera - Max 30fps@1080P · HD and SD output switchable, - 2.8mm/3.6mm fixed lens · 10m/110°detecting range/angle · Max. IR length 20m, Smart IR · IP67, DC12V 				
42	DH-HAC-HDW1200RP	<ul style="list-style-type: none"> 2MP HDCVI IR Eyeball Camera · Max 30fps@1080p(1920x1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm optional) · Max. IR length 20m, Smart IR · DC12V 				
43	DH-HAC-HDBW1200EP	<ul style="list-style-type: none"> · 2MP HDCVI IR Dome Camera · Max 30fps@1080P · IP67, IK10, DC12V · HD and SD output switchable · 3.6mm fixed lens (2.8mm optional) · Max. IR length 30m, Smart IR 				
45	DH-HAC-HDW1200EMP-A-0280B-S5	<ul style="list-style-type: none"> · 2MP HDCVI IR Eyeball Camera · Max 30fps@1080P(1920x1080) · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 50m, Smart IR · IP67, DC12V, Built in mic 	IRR 11,370,000	IRR 11,800,000		
46	DH-HAC-HDW1209TLQP-LED-0280B	<ul style="list-style-type: none"> · 2MP Full-color Starlight HDCVI Eyeball Camera · Full-color starlight · 20 m illumination distance, · Max. 30fps @ 1080P · CVI / CVBS / AHD / TVI switchable · Fixed lens (2.8 mm; 3.6 mm optional) · IP67, 12V ± 30% DC · Max 30fps@1080P 	IRR 10,420,000	IRR 11,050,000	IRR 9,630,000	
47	DH-HAC-HDW1200TLMQP-0208B	<ul style="list-style-type: none"> · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 3.6mm fixed lens (2.8mm optional) · Built-in mic(-A) · Max. IR length 30m, Smart IR 		IRR 10,150,000		
48	DH-HAC-HFW1200TLP-0360B-S5	<ul style="list-style-type: none"> 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V 	IRR 10,630,000			
49	DH-HAC-HFW1200TLP-A	<ul style="list-style-type: none"> 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6 & 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2D-DNR Max. IR LEDs length 40m, Smart IR, IP67, DC12V--a 	IRR 11,900,000			
50	DH-HAC-HFW1200TL-A	<ul style="list-style-type: none"> 2MP HDCVI IR Bullet Camera- Max 30fps@1080P · CVI/CVBS/AHD/TVI switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Built-in mic · Max. IR length 80m, Smart IR · IP67, DC12V 	IRR 10,900,000			
51	DH-HAC-HFW1200TP(S)	<ul style="list-style-type: none"> 1/2.7" 2Megapixel CMOS .Max 30fps@1080P · HD and SD output switchable · 3.6mm fixed lens (2.8mm, 6mm optional) · Max. IR length 30m, Smart IR · IP67, DC12V 	IRR 10,310,000	IRR 10,500,000		
52	DH-HAC-HFW1200TP-A-0360B-S5	<ul style="list-style-type: none"> 1/2.7" Progressive Scan 2Megapixel CMOS.Max 30fps@1080P HD and SD output switchable Built-in mic 2.8mm fixed lens Max. IR length 30m, Smart IR IP67, DC12V 	IRR 10,550,000	IRR 11,200,000		
53	DH-HAC-HFW1200DP-S5-0360B	<ul style="list-style-type: none"> 1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P DWDR, Day/Night(ICR), AWB, AGC, HLC, BLC, 2D-DNR HD and SD output switchable, 3.6mm fixed lens Max. IR LEDs length 80m, Smart IR, IP67, DC12V 	IRR 13,480,000	IRR 14,000,000		
54	DH-HAC-HFW1200RP(S)	<ul style="list-style-type: none"> 1/2.7" 2Megapixel CMOS25/30fps@1080P, 25/30/50/60fps@720P 3.6mm fixed lensHD and SD output switchableDay/Night(ICR), AWB, AGC, BLC, 2D-DNRSupport OSD MenuMax IR length 20m, Smart IR IP67 				
55	DH-HAC-HDW1209TLQP-A-LED-0280B	<ul style="list-style-type: none"> 2MP Full-color HDCVI Quick-to-install Eyeball Camera 1/2.8 inch 2MP Progressive CMOS Max. 30fps@1080P 2.8mm fixed lens Built-in Mic Max 30fps@1080P 	IRR 11,220,000			
57	DH-HAC-HDW1200TMQP-A-S5-0280B	<ul style="list-style-type: none"> · Quick-to-install eyeball saves installation time · CVI/CVBS/AHD/TVI switchable · 2.7-12mm motorized lens · Built-in mic(-A) · Max. IR length 60m, Smart IR 		IRR 12,750,000		

58	DH-HAC-HDW1200TRQP-A-0360B-S5	2MP HDCVI Quick-to-Install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu	IRR 10,420,000			
59	DH-HAC-HDW1200TRQP-A-0280B-S5	2MP HDCVI Quick-to-Install IR Eyeball Camera 1/2.7 inch Progressive CMOS Max 30fps@2MP 2.8mm/3.6mm fixed lens Built in Mic CVI/TVI/AHD/CVBS Switchable, Support OSD Menu	IRR 10,420,000	IRR 9,750,000		
60	DH-HAC-HFW1200SP	Max 30fps@1080P(1920x1080) 2MP HDCVI IR Bullet Camera HD and SD output switchable 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 30m, Smart IR - IP67, DC12V				
64	DH-HAC-HFW1230TLP	2MP Starlight HDCVI IR Bullet Camera Max. 30fps@1080P HD and SD output switchable 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 40m, Smart IR - IP67, DC12V				
65	DH-HAC-HFW1230TP	2MP Starlight HDCVI IR Bullet Camera Max. 30fps@1080P, Starlight HD and SD output switchable 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 30m, Smart IR - IP67, DC12V				
66	DH-HAC-HFW1230THP-I8	2MP Starlight HDCVI IR Bullet Camera Max. 30fps@1080P HD and SD output switchable 3.6mm fixed lens (6mm, 8mm optional) Max. IR length 80m, Smart IR - IP67, DC12V				
67	DH-HAC-HFW1200THP-I8	2MP HDCVI IR Bullet Camera Max. 30fps@1080P HD and SD output switchable 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 80m, Smart IR - IP67, DC12V	IRR 13,100,000	IRR 12,500,000		
68	DH-HAC-HFW1200THP-I4	DH-HAC-HFW1200THP-I4 2MP HDCVI IR Bullet Camera * The parameters and datasheets below can only be applied to 1200-S5 series > Max 30fps@1080P > HD and SD output switchable> 3.6mm fixed lens (2.8mm, 6mm optional) > Max. IR length 40m, Smart IR - IP67, DC12V	IRR 12,310,000	IRR 11,500,000		
71	DH-HAC-HFW1200RP-Z-IRE6	Max 30fps@1080P(1920x1080) HD and SD output switchable 2.7-12mm Motorized lens Max. IR length 60m, Smart IR - IP67, DC12V	IRR 23,010,000			
72	DH-HAC-HFW1209CP-LED-0280B	Full-color starlight 20 m illumination distance Max. 30fps@1080P, CVI/CVBS/AHD/TVI switchable Fixed lens (2.8 mm; 3.6 mm optional) IP67, 12V±30% DC		IRR 10,200,000		
73	DH-HAC-HFW1209CP-LED-0360B	Full-color starlight 20 m illumination distance Max. 30fps@1080P, CVI/CVBS/AHD/TVI switchable Fixed lens (2.8 mm; 3.6 mm optional) IP67, 12V±30% DC	IRR 10,020,000			
74	DH-HAC-HFW1200CMP	2 MP HDCVI Bullet Camera with IR Illumination > Up to 30fps @ 1080P > Switchable CVI / CVBS / AHD / TVI outputs > Fixed lens 3.6mm (2.8mm optional), > Built-in microphone (A) > Max. IR illumination range 30m, Intelligent IR illumination > IP67, DC 12V	IRR 10,320,000			
75	DH-HAC-HFW1200CMP-A	HAC-HFW1200CM-A-POC 2MP HDCVI POC Fixed IR ullet Camera> Max 30 fps@1080P. > 3.6mm fixed lens (2.8mm optional)> CVI/CVBS/AHD/TVI switchable. > Built-in mic> Max. IR length 30m, Smart IR.> IP67, PoC (only CVI)/12V±30% DC.	IRR 11,110,000			
76	DH-HAC-HFW1209CMP-LED-0360B	2MP Full-color HDCVI Bullet Camera > 24/7 color imaging > 20 m illumination distance > Max. 30 fps @ 1080p, > Built-in mic (A) > CVI / CVBS / AHD / TVI switchable > Fixed lens (2.8 mm; 3.6 mm optional), > IP67, 12V ± 30% DC	IRR 11,210,000			
77	DH-HAC-HFW1239TP-LED	Full-color starlight 20m LED distance Max. 30fps@1080P, CVI/CVBS/AHD/TVI Switchable 3.6mm fixed lens (2.8mm Optional) IP67, DC12V±30% DC	IRR 15,080,000			
78	DH-HAC-HFW1231RP-Z-A	2MP Starlight HDCVI IR Bullet Camera > Max. 30 fps@1080P > Starlight, 130dB true WDR, 3D NR > Auto focus, 2.7 mm-12 mm motorized lens > CVI/CVBS/AHD/TVI switchable Super Adapt > Built-in mic> Max. IR length 80 m, Smart IR	IRR 26,980,000			
79	DH-HAC-HFW1400TLP	Max. 30fps@4MP HD and SD output switchable 3.6mm fixed lens (2.8mm, 6mm optional) Max. IR length 40m, Smart IR - IP67, DC12V				
80	DH-HAC-HFW1400THP-I8	4MP HDCVI IR Bullet Camera Max. 30fps@4MP - IP67, DC12V HD and SD output switchable 3.6mm fixed lens (6mm, 8mm optional) Max. IR length 80m, Smart IR				
81	HAC-HDW1200MP-S5-0280B	Dahua DH-HAC-HDW1200MP-0280B-S5 Dahua 4 in 1 fixed dome with... Dahua 4 in 1 fixed dome with Smart IR 30m for outdoor use. CMOS 1/2.7" 2MP. Output 4 in 1 by a BNC port. Fixed optics 2.8 mm (101°), 0.02 lux. ICR filter. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D-NR, Mirror, privacy masks. 3AXIS. 12V DC.	IRR 10,320,000	IRR 10,350,000		
82	HAC-HDW1200M-S5	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 3.6mm fixed lens HD and SD output switchable, Support OSD Menu Day/Night(ICR), AWB, AGC, BLC, 2D-DNR Max. IR length 30m, Smart IR, IP67, DC12V	IRR 9,180,000			
83	COOPER		P			
84	DH-HAC-B2A51P-0360B-S2	20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium	IRR 13,680,000			

85	DH-HAC-B2A51P-0208B-S2	20fps@5MP, 25/30fps@4MP & @1080P (16:9 video output) 3.6mm & 2.8mm fixed lens DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR HD and SD output switchable, Support OSD Menu Max. IR length 20m, IP67, DC12V, Casing: Aluminium	IRR 13,680,000	IRR 13,550,000	
86	DH-HAC-B2A21P-0280B	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium		IRR 8,600,000	
87	DH-HAC-B2A21P-0360B	1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P, 3.6mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 9,070,000		
88	DH-HAC-T2A21P-0280B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 9,520,000	IRR 8,850,000	
89	DH-HAC-T2A21P-0360B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, IP67, DC12V, Casing: Aluminium	IRR 8,430,000		
90	DH-HAC-T1A21P-0280B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm & 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V	IRR 7,890,000	IRR 7,050,000	
91	DH-HAC-T1A21P-0360B	1/2.7" 2Megapixel CMOS, 25/30fps@1080P, 50/60fps@720P 2.8mm & 3.6 fixed lens HD and SD output switchable, Support OSD Menu DWDR, Day/Night(ICR), AWB, AGC, BLC, HLC, 2DNR Max. IR length 20m, Smart IR, Casing: Plastic, DC12V	IRR 7,060,000		
92	DH-HAC-T1A41P	. 4MP HDCVI IR Eyeball Camera . Max. 30fps@4MP (2560x1440) . HD and SD output switchable . 3.6mm fixed lens (2.8mm, 6mm optional) . Max. IR length 20m, Smart IR. DC12V			
93	HAC-D1A51P			IRR 11,500,000	
94	HAC-T1A51P			IRR 11,780,000	
95	DH-HAC-T2A41P	. Max. 30fps@4MP(2560x1440) . HD and SD output switchable . 3.6mm fixed lens (2.8mm,6mm optional) . Max. IR length 20m, Smart IR - IP67, DC12V			
96	DH-HAC-T2A51P	. 5MP HDCVI IR Eyeball Camera . Max. 20fps@5MP (2592x1944) . HD and SD output switchable . 3.6mm fixed lens (2.8mm,6mm optional) . Max. IR length 20m, Smart IR. IP67, DC12V	IRR 14,280,000	IRR 13,000,000	
97	DH-HAC-B1A21P	. 2MP HDCVI IR Bullet Camera . Max. 30fps@1080P (1920x1080) . HD and SD output switchable . 3.6mm fixed lens (2.8mm, 6mm optional) . Max. IR length 20m, Smart IR. IP67, DC12V	IRR 8,000,000	IRR 7,050,000	
98	DH-HAC-B1A41P	. 4MP HDCVI IR Bullet Camera . Max. 30fps@4MP (2560x1440) . HD and SD output switchable . 3.6mm fixed lens (6mm optional) . Max. IR length 20m, Smart IR. IP67, DC12V			
99	DH-HAC-B1A51P	5MP HDCVI Fixed IR Bullet Camera * The parameters and datasheets below can only be applied to A51-S2 series * In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must be upgraded to V4.001.0000001.0.R.200908 or later version-> Max. 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable-> 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 20 m, Smart IR-> IP67, DC12V	IRR 12,700,000	IRR 11,800,000	
100	DH-HAC-B2A41P	. Max. 30fps@4MP(2560x1440) . HD and SD output switchable . 3.6mm fixed lens (2.8mm,6mm optional) . Max. IR length 20m, Smart IR - IP67, DC12V			
101	DH-HAC-B2A41P	2MP 15x Starlight HDCVI PTZ Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 15x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IR distance up to 100 m > IP66	IRR 128,560,000		
102	PTZ	XVR	P		
103	DH-SD49225-HC-LA	2MP 25x Starlight IR PTZ HDCVI Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P > IR distance up to 100 m > IP66			
104	DH-SD59230I-HC	. 1/2.8" 2Megapixel STARVIS™ CMOS . Powerful 30x optical zoom . Starlight technology . 120dB true WDR, 3D DNR . Max. 25/30fps@1080P, 25/30/50/60fps@720P . IR distance up to 150m · IP66			
105	DH-SD59232-HC-LA	2MP 32x Starlight IR PTZ HDCVI Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32X optical zoom > Starlight technology > 120dB true WDR, 3D DNR > Max. 25/30 fps@1080P, 25/30/50/60 fps@720P	IRR 238,950,000		

106	DH-SD594301-HC	<ul style="list-style-type: none"> · 1/3" 4Megapixel CMOS · Powerful 30x optical zoom · 120dB true WDR, 3D DNR · Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P · IR distance up to 100m · IP66 				
107	XVR	XVR	P			
108	XVR1B04-I	<ul style="list-style-type: none"> · 4 Channel Penta-brid 1080N/720p Real-time WizSense AI XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+1 IP up to 2MP(20 Mbps), · 4CH: 1/4 PlaybackHDMI , VGA ,simultaneous video Output1 SATA port, up to 6 TB capacity2*USB 2.0, 10/100 Mbps LAN Interface, P2P SupportSMD Plus, Full channel AI-Coding, Human/Vehicle Classification 	IRR 20,990,000	IRR 17,500,000	IRR 16,800,000	
109	DH-XVR1A08	<ul style="list-style-type: none"> · 8 Channel Penta-brid 1080N/720P Cooper 1U · H.264 video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 10 channels IP camera inputs, each channel up to 5MP; Max 40Mbps Incoming Bandwidth · Long transmission distance over coax cable 	IRR 23,100,000			
110	DH-XVR1A04	<ul style="list-style-type: none"> · 4Channel Penta-brid 1080N/720P Cooper 1U · H.264 video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 5channels IP camera inputs, each channel up to 2MP; Max 20Mbps Incoming Bandwidth · Long transmission distance over coax cable 				
111	DH-XVR1B08-I	<ul style="list-style-type: none"> · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [8+2 IP up to 6MP(40 Mbps), · 4CH: 1/4/9 PlaybackHDMI , VGA ,simultaneous video Output · 1 SATA port, up to 6 TB capacity2*USB 2.0, 10/100 Mbps LAN Interface, P2P Support · 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification 	IRR 26,000,000	IRR 22,000,000	IRR 21,200,000	
112	DH-XVR1B16-I	<ul style="list-style-type: none"> · H.265+/H.265 dual-stream video compression1st channel 1080N/720P@25fps, others 1080N/720P@15fps16CH: 1/4/9/16 Playback · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [16+2 IP up to 6 MP(72 Mbps)]1 Audio Input / 1 Audio Output, 1 SATA Port , Up to 6 TBHDMI , VGA ,simultaneous video Output · 2 USB 2 , 10/100 Mbps LAN Interface, P2P Support 	IRR 43,520,000	IRR 43,950,000		
113	DH-XVR1B16H	<ul style="list-style-type: none"> · .16 Channel Penta-brid 4M-N/1080P Cooper 1U 1HDD Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 96Mbps incoming bandwidth , Long transmission distance over coax cable · Supports 1 SATA HDD, up to 6TB , Smart Search and Intelligent Video System 				
114	DH-XVR4104HS-I	<ul style="list-style-type: none"> · .4 Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 5 channels IP camera inputs, each channel up to 2MP; Max 32 Mbps incoming bandwidth · Up to 4 channels video stream (analog channel) SMD Plus 		IRR 23,900,000		
115	DH-XVR4108HS-I	<ul style="list-style-type: none"> · .8 Channel Penta-brid 1080N/720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 10 channels IP camera inputs, each channel up to 6MP; Max 32 Mbps incoming bandwidth · Up to 8 channels video stream (analog channel) SMD Plus 		IRR 29,670,000		
116	DH-XVR4116HS-I	<ul style="list-style-type: none"> · .16 Channel Penta-brid 720p Compact 1U 1HDD WizSense Digital Video Recorder · H.265+/H.265 video compression · Supports Full-channel AI-Coding · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 18 channels IP camera inputs, each channel up to 6MP; Max 64 Mbps Incoming Bandwidth · Long transmission distance over coax cable 	IRR 51,270,000			
117	DH-XVR5104HS-I3	<ul style="list-style-type: none"> · 4 Channel Penta-brid 5M-N/1080p None Real-time WizSense AI XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M [4+2 IP up to 6MP(32 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4ch1 SATA Port up to 6 TB capacity2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Classification, IoT Support 	IRR 30,000,000	IRR 29,200,000	IRR 28,200,000	
118	DH-XVR5108HS-I3	<ul style="list-style-type: none"> · 8 Channel Penta-brid 5M-N/1080p None Real-time WizSense AI XVR · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS) N+M 8+4 IP up to 6MP(64 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity 	IRR 45,100,000	IRR 30,800,000		
119	DH-XVR5104HS-4KL-I3	<ul style="list-style-type: none"> · 4 Channel Penta-brid 4K WizSense AI XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 4+4 IP up to 8MP(64 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4ch1 SATA Port up to 10 TB capacity2*USB 2.0, RS485, 10/100 Mbps LAN Interface, P2P Support · 1ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 1ch FaceRecognition up to 10,000 Face Library, 4ch SMD Plus, Full channel AI-Coding, Human/Vehicle Classification, IoT Support 	IRR 43,570,000	IRR 43,640,000		
120	DH-XVR5108HS-4KL-I3	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense AI XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Classification, IoT Support 	IRR 76,900,000			
121	DH-XVR5108HS-4KL-I2	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense AI XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Classification, IoT Support 	IRR 68,730,000			
122	DH-XVR5108HS-4KL	<ul style="list-style-type: none"> · 8 Channel Penta-brid 4K-N/5MP WizSense AI XVR · 4K@7fps, 6MP@10fps, 5MP@12fps, 4K-N/4MP@15fps, 4MN/1080p/720p@25/30fps · H.265+/H.265/H.264+/H.264 dual-stream video compression · Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 8+8 IP up to 8MP(128 Mbps) · HDMI/VGA Simultaneous Video Output, 1ch Audio I/O · Playback 1/4/9ch · 1 SATA Port up to 10 TB capacity1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 8ch SMD Plus, Human/Vehicle Classification, IoT Support 	IRR 74,700,000			
123	DH-XVR5116H-I2	<ul style="list-style-type: none"> · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 6MP; Max 128 Mbps incoming bandwidth · Up to 2 channels video stream (analog channel) Perimeter Protection · Up to 16 channels video stream (analog channel) SMD Plus · Up to 2 channels video stream (analog channel) human face recognition · IoT & POS functionalities 	IRR 72,130,000			
	DH-XVR5116HS-I3			IRR 76,000,000		

124	DH-XVR5116HS-S2	16 Channel Penta-brid 1080P Compact 1U Digital Video Recorder > Embedded processor-Power Supply DC12V/2A > H.264+/H.264 video compression > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6/12/24 channels IP camera inputs, each channel up > Smart Search and Intelligent Video System-Internal HDD 1 SATA Port, up to 8TB capacity	IRR 72,480,000		
125	DHI-XVR5216AN-S2	Embedded processor > H.264+/H.264 dual-stream video compression > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 6/12/24 channels IP camera inputs, each channel up > Smart Search and Intelligent Video System	IRR 94,500,000		
126	DH-XVR5216AN-I2	16 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+4 IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support	IRR 74,810,000		
127	DH-XVR5216AN-4KL	16 Channel Penta-brid 4K 1U Digital Video Recorder -Embedded processor – H.264+/H.264 dual-stream video compression – Support HDCVI/AHD/TVI/CVBS/IP video inputs – Max 12/24 channels IP camera inputs, each channel up to 8MP – Max 48/96Mbps Incoming Bandwidth – Smart Search and Intelligent Video System	IRR 136,370,000		
128	DH-XVR5216AN-4KL-I2	16 Channel Penta-brid 4KN/5MP WizSense Ai XVR 4K@7fps, 6MP@10fps, 5MN@12fps, 4KN/4MP@15fps, 4MN/2MP/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 16+16 IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 20,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support	IRR 140,850,000		
129	DHI-XVR5232AN-S2	Embedded processor ·H.264+/H.264 dual-stream video compression ·Support HDCVI/AHD/TVI/CVBS/IP video inputs ·Max 32 channels IP camera inputs; Max 128Mbps Incoming Bandwidth ·Long transmission distance over coax cable ·Support 2 SATA HDD, up to 16TB	IRR 142,300,000		
130	DH-XVR5232AN-I2	32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 6MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 1ch Audio I/O Playback 1/4/9/16ch 2 SATA Port up to 10 TB capacity each port(20TB Total) 1*USB 2.0, 1*USB 3.0, RS485, 1*1000 Mbps LAN Interface, RS485, P2P Support 2ch Perimeter(Tripwire/Intrusion) 10 IVS each channel, 2ch FaceRecognition up to 10,000 Face Library, 16ch SMD Plus, Human/Vehicle Classification, IoT Support	IRR 120,270,000		
131	DH-XVR5104HS-4KL-I2	4 Channel Penta-brid 4K-N/5MP Compact 1U 1HDD WizSense Digital Video Recorder ·H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 8 channels IP camera inputs, each channel up to 8MP; Max 64 Mbps incoming bandwidth ·Up to 2 channels video stream (analog channel) Perimeter Protection			
132	DH-XVR5216AN-4KL-X	16 Channel Penta-brid 4K 1U Digital Video Recorder · H.265+/H.265 dual-stream video compression · Supports HDCVI/AHD/TVI/CVBS/IP video inputs · Max 12/24 channels IP camera inputs, each channel up to 8MP; Max 48/96Mbps Incoming Bandwidth · Smart Search and Intelligent Video System			
133	DH-XVR5432L-I2	32 Channel Penta-brid 5M-N/1080P WizSense Ai XVR 5MN@10fps, 4MN/2MP@15fps, 2MN/1MP@25/30fps H.265+/H.265/H.264+/H.264 dual-stream video compression Pentabrid (IP+CVI+AHD+TVI+CVBS)N+M 32ch IP up to 8MP(128 Mbps) HDMI/VGA Simultaneous Video Output, 4/1ch Audio I/O, 16/6 Alarm I/O Playback 1/4/9/16ch	IRR 181,870,000		
134	PINHOLE				
135	DH-HAC-HUM2301BP-B		IRR 19,360,000		
136	D.D.C PERSIA Tel/Fax : 98 21 88 54 18 00 98 21 88 55 55 58 98 21 88 10 20 01 - 5 www.ddcpersia.com info@ddcpersia.com				

