www.ddcpersia.com

## ليست قيمت

## (HIKVISION)

شماره تماس: ۲۱-۵٤۸۷۱۰۰۰

	NELWOIK CAIHEIA - IVVI			
	Items	Description	User Price	
	Lite Mini Bullet Series			
1	DS-2CD1023G0E-I	2.0 MP IR Network Bullet Camera -1/2.8" progressive scan CMOS - Max. Frame Rate: 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720 - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67 - Dual stream - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 21,380,000	Januaria .
2	DS-2CD1021G0E-I	Hikvision 2MP Mini IR Network Bullet camera, 1/2.8" Progressive CMOS, ICR, 1920x1080:20fps (P)/(N), H.265 / H.264+ & H.264, 3D DNR, BLC, IR range: up to 30m, DC12V & POE  Rs. 0.001Is our price higher or showing zero? Please chat now and ask for the best price. Prices if shown are inclusive of applicable taxes. Tax rate may be adjusted as per customer's taxation status. For supply of product only, excluding any cabling and/or installation. Shipping charges can sometimes vary.	IRR 13,932,000	ANN HAVINGA
	DS-2CD1023G0-I		IRR 23,500,000	ANK SPIAGN
3	DS-2CD1023G0-IUF	High quality imaging with 2 MP resolution, Efficient H.265+ compression technology, Clear imaging against strong back light due to DWDR technology, Water and dust resistant (IP67), EXIR 2.0: advanced infrared technology with long IR range, Support up to 256 GB SD card storage, Built-in microphone for real-time audio security	IRR 31,770,000	AMILIFICATIV -
4	DS-2CD1047G0-L ColorVu Lite	4 MP <u>ColorVu Lite</u> Fixed Bullet Network Camera, High quality imaging with 4 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	IRR 38,760,000	and in
5	DS-2CD1043G0-I	4.0 MP IR Network Bullet Camera, 1/3" progressive scan CMOS , 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 , IP67, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 31,500,000	ABK INVADA
6	DS-2CD1057G0-L	5MP ColorVu Lite Fixed Bullet Network Camera, High quality imaging with 5 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7	IRR 45,920,000	000
7	DS-2CD1053G0-I	5 MP Fixed Bullet Network Camera High quality imaging with 5 MP resolution. Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR <sub>3</sub> (IP67) EXIR 2.0: advanced infrared technology with long IR range -UF: Built-in microphone for real-time audio security	IRR 31,370,000	ABK INVADA
8	Lite Dome Series			
9	DS-2CD1323G0E-I	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67	IRR 20,940,000	name of the same o
10	DS-2CD1323G0-IUF (2.8)	1/2.8" progressive scan CMOS - 1920 × 1080@30fps - 2.8 mm/4 mm/6 mm fixed lens - H.264+, H.264 - Dual stream - Digital WDR (Wide Dynamic Range) - 3D DNR (Digital Noise Reduction) - Up to 30 m IR range - PoE (Power over Ethernet) - IP67 - <b>Built-in microphone</b>	IRR 27,110,000	**************************************

11	DS-2CD1327G0-L ColorVu	2 MP <u>ColorVu Lite</u> Fixed Turret Network Camera, High quality imaging with 2 MP resolution Excellent low-light performance, Efficient H.265+ compression technology, Water and dust resistant (IP67), 24/7 colorful imaging	32,160,000	ANGENTA DE LA CONTROL DE LA CO
12	DS-2CD1347G0-L ColorVu	High quality imaging with 4 MP resolution. Excellent low-light performance. Efficient H.265+ compression technology.  Water and dust resistant (IP67). 24/7 colorful imaging.	IRR 57,790,000	ASSESSIVE OF THE PARTY OF THE P
13	DS-2CD1123G0E-I	2MP dome Exir, fixed lens 2.8mm,white color-1/2.8" progressive scan CMOS - 3D DNR (Digital Noise Reduction) - 1920 × 1080@30fps - Up to 30 m IR range - 2.8 mm/4 mm/6 mm fixed lens - PoE (Power over Ethernet) - H.265+, H.265, H.264+, H.264 - IP67, IK10 - Digital WDR (Wide Dynamic Range) - ECO CASE	IRR 23,190,000	AND STREET
14	DS-2CD2126G2-ISU 2.8mm	2 MP AcuSense Fixed Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle classification based on deep learning -SU: Built-in microphone for real-time audio security, Audio and alarm interface available Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 63,530,000	AAAAAAA TA'AAAAA TA'AAAAAA TA'AAAAAA TA'AAAAAA TA'AAAAAA TA'AAAAAAA TA'AAAAAAAA
15	DS-2CD2123G2-I (2.8)	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 41,920,000	March Control of the
	DS-2CD2125FHWD-IS	2 MP High Frame Rate Fixed Dome Network Camera High quality imaging with 2 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  High frame rate video to illustrate smooth movement	IRR 49,060,000	2003000
	DS-2CD2H25FWD-IZS	2 MP Powered-by-DarkFighter Varifocal Turret Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP66) and vandal proof (IK10)	IRR 108,180,000	- American
16	DS-2CD1143G0-I	4.0 MP IR Network Dome Camera, 1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction), 2560 × 1440@20fps - Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens ,PoE (Power over Ethernet), H.265+, H.265, H.264+, H.264 - IP67, IK10, Dual stream, Digital WDR (Wide Dynamic Range)	IRR 34,790,000	MANAGE PARTY OF THE PARTY OF TH
	DS-2CD1143G0-IUF		IRR 39,620,000	A00 30 30 50 50 50 50 50 50 50 50 50 50 50 50 50
	DS-2CD1153G0-I	5 MP Fixed Dome Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) and vandal resistant (IK10) EXIR 2.0: advanced infrared technology with long IR range	IRR 43,860,000	ANCHANA .
17	Mini Bullet Series			
18	DS-2CD2025FWD-I	2 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology, Efficient H.265+ compression technology,Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP67),Robust structure design with full metal material.	42,050,000	
19	DS-2CD2021G1-I (2.8)	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Support up to 256 GB SD card storage	IRR 38,930,000	
20	DS-2CD2023G2-I (2.8)	High quality imaging with 2 MP resolution Clear imaging against strong backlight due to <b>120 dB WDR</b> technology Efficient H.265+ compression technology Water and dust resistant ( <b>IP67</b> ) Focus on human and vehicle targets classification based on deep learning	IRR 42,810,000	
21	DS-2CD2027G2-L (2.8)	High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB WDR technology 24/7 colorful imaging Focus on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 55,340,000	47000 (1)

	DS-2CD2043G2-I 2.8mm	4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology -U: Built-in microphone for real-time audio security Water and dust resistant (IP67) Focus on human and vehicle targets classification based on deep learning	IRR 53,920,000	Autread S
	DS-2CD2043G0-IU (2.8)		IRR 55,990,000	Autreau Control
	DS-2CD2045FWD-I	4 MP Powered-by-DarkFighter Fixed Mini Bullet Network Camera High quality imaging with 4 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Water and dust resistant (IP67)  Robust structure design with full metal material.	IRR 44,380,000	
23	<b>DS-2CD2047G2-L</b> (2.8)	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IR67)	IRR 47,650,000	The same of the sa
24	DS-2CD2063G2-I	6 MP IR Fixed Bullet Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 46,070,000	
	DS-2CD2063G2-I2.8mm	6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning -U: Built-in microphone for real-time audio security Water and dust resistant (IP67)	IRR 46,070,000	Andre Sign
25	DS-2CD2083G2-I (2.8)	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI/HLC - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB	IRR 54,810,000	
	DS-2CD2083G2-I2.8mm	8 MP AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning -U: Built-in microphone for real-time audio security Water and dust resistant (IP67)	IRR 54,810,000	
	DS-2CD2087G2-LU (2.8MM)	4 K ColorVu Fixed Bullet Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 130 dB WDR technology Focus on human and vehicle classification based on deep learning 24/7 colorful imaging Built-in microphone for real-time audio security (-U)	IRR 110,790,000	NOOP - 11
26	Dome Series			
27	DS-2CD2143G2-IU	4 MP Vandal Built-in Mic Fixed Dome Network Camera  High quality imaging with 4 MP resolution  Clear imaging against strong backlight due to 120 dB WDR technology, Efficient H.265+ compression technology, Built-  in microphone for real-time audio security  Water and dust resistant (IP67) and vandal resistant (IK10)  Focus on human and vehicle targets classification based on deep learning	IRR 44,980,000	
28	DS-2CD2347G2-L (2.8)	High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Built-in microphone for real-time audio security(-U) Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IP67)	IRR 61,480,000	

	DS-2CD2347G2-LU (2.8)		IRR 63,530,000	0
29	DS-2CD1353G0-I (2.8 MM)	5MP Fixed Turret Network Camera High quality imaging with 5 MP resolution Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR Water and dust resistant (IP67) EXIR 2.0: advanced infrared technology with long IR range -UE: Built-in microphone for real-time audio security	IRR 41,640,000	4-7 2-8
30	DS-2CD1357G0-L	5MP ColorVu Lite Fixed Turret Network Camera High quality imaging with 5 MP resolution Excellent low-light performance Efficient H.265+ compression technology Water and dust resistant (IP67) 24/7 colorful imaging	IRR 45,920,000	A.
	DS-2CD2145FWD-IS	4 MP Powered-by-DarkFighter Fixed Dome Network Camera  High quality imaging with 4 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Standio and alarm interface available  4 MP AcuSense Fixed Dome Network Camera	IRR 49,060,000	as many
	DS-2CD2146G2-I	4 MP AcuSense Fixed Dome Network Camera High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology  Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning  Built-in microphone for real-time auto security(-SUI)  4 MP ColorVu Fixed Dome Network Camera	IRR 49,240,000	ALLEGAL STATES
	DS-2CD2147G2-LSU (2.8mm)	High quality imaging with 4 MP resolution  Efficient H.265+ compression technology  Clear imaging against strong back light due to 130 dB WDR technology  24/7 colorful imaging  Focus on human and vehicle targets classification based on deep learning	IRR 57,200,000	ALIGHW CONTRACTOR OF THE PARTY
31	DS-2CD2163G2-IU	6 MP IR Fixed Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP66 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - <b>Built-in microphone</b>	IRR 46,870,000	ALEGEN .
	DS-2CD2166G2-I (2.8mm)	High quality imaging with 6 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Focus on human and vehicle targets classification based on deep learning  Built-in microphone for real-time audio security (-SU)  Audio and alarm interface available(-SU)  Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 53,050,000	NA HOUSE
32	DS-2CD2183G2-IU	8 MP AcuSense Vandal Fixed Dome Network Camera High quality imaging with 8 MP resolution Clear imaging against strong backlight due to 120 dB true WDR technology Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security Water and dust resistant (IP67) and vandal-resistant (IK10) 4K Acusense Fixed Dome Network Camera	IRR 51,650,000	at resum
	DS-2CD2186G2-I (2.8mm)	4K Acusense Fixed Dome Network Camera High quality imaging with 8 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Built-in microphone for real-time audio security (-SU) Audio and alarm interface available(-SU) Water and dust resistant (IP67) and vandal resistant (IK10)	IRR 65,930,000	ASSESSED
33	DS-2CD2183G0-IS	8 MP IR Fixed Dome Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.5" Progressive Scan CMOS - 3840 × 2160 @15 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection -120dB WDR - S: Audio/Alarm IO connectors	IRR 48,790,000	renzus,

	DS-2CD2185FWD-IS	4K Fixed Dome Network Camera High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -S: audio and alarm interface available Water and dust resistant (IP67) and vandal proof (IK10) Robust structure design with full metal materials.	IRR 65,070,000	AFTON
34	Bullet Series			
35	DS-2CD2T43G0-I5	1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 50m IR range	IRR 46,400,000	<b>6</b>
36	DS-2CD2T43G0-I8	1/3" Progressive Scan CMOS,2688 ×1520@30fps,2.8/4/6/8mm fixed lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR, H.265+, H.265, H.264+, H.264,Three streams,120dB WDR,2 Behavior analyses, and face detection,BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB-up to 80m IR range	IRR 48,100,000	The state of the s
37	DS-2CD2T43G2-2I (2.8)	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67)2I: up to 60 m Focus on human and vehicle targets classification based on deep learning 2.8mm	IRR 58,630,000	<b>5</b>
38	DS-2CD2T43G2-4I (4mm)	High quality imaging with 4 MP resolution Clear imaging against strong backlight due to 120 dB WDR technology Efficient H.265+ compression technology Water and dust resistant (IP67)4I: up to 80 m Focus on human and vehicle targets classification based on deep learning 4mm	IRR 65,480,000	acre .
	DS-2CD2T45FWD-I5 lenz4	4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Water and dust resistant (IP67)	IRR 52,170,000	
	DS-2CD2T45FWD-I82.8mm	4 MP Powered-by-DarkFighter Fixed Bullet Network Camera High quality imaging with 4 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) Robust structure design with full metal materials	IRR 54,510,000	The state of the s
	DS-2CD2T46G2-4I (2.8mm)	4 MP AcuSense Fixed Bullet Network Camera High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology Clear imaging against strong backlight due to 120 dB true WDR technology  Efficient H.265+ compression technology Focus on human and vehicle targets classification based on deep learning	IRR 57,190,000	
	DS-2CD2T46G2-ISU/SL2.8mm	4 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera  High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  Clear imaging against strong backlight due to 120 dB true WDR technology  Efficient H.265+ compression technology  Focus on human and vehicle targets classification based on deep learning  Active Standard India places to suppose introduce off	IRR 60,360,000	The same of the sa
	Ds-2CD2T47G2-L	4 MP ColorVu Fixed Bullet Network Camera High quality imaging with 4 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 130 dB WDR technology Focus on human and vehicle targets classification based on deep learning 24/7 colorful imaging Water and dust resistant (IB67)	IRR 57,980,000	and the same of th
39	DS-2CD2T63G0-l8	6 MP IR Fixed Bullet Network Camera - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps - 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - up to 80m IR range	IRR 52,700,000	6-0
40	DS-2CD2T63G2-4I(4MM)	High quality imaging with 6 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 64,510,000	<b>5</b>

	DS-2CD2T66G2-2I (2.8mm)	6 MP AcuSense Fixed Bullet Network Camera High quality imaging with 6 MP resolution Excellent low-light performance with powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Water and dust resistant (IP67)	IRR 58,980,000	6
41	DS-2CD2T83G0-l8	8 MP IR Fixed Bullet Network Camera - 1/2.5" Progressive Scan CMOS -3840 × 2160 @15 fps 2.8/4/6/8 mm fixed lens - Color: 0.01 lux @(F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR - H.265+, H.265, H.264+, H.264 - 2 Behavior analyses and face detection - 120dB WDR - BLC/3D DNR/ROI - IP67 - Built-in micro SD/SDHC/SDXC card slot, up to 128 G-up to 80m IR range	IRR 55,760,000	<b>6</b>
42	DS-2CD2T83G2-4I(4MM)	High quality imaging with 8 MP resolution Efficient H.265+ compression technology Clear imaging against strong backlight due to 120 dB WDR technology Focusing on human and vehicle classification based on deep learning Water and dust resistant (IP67)	IRR 57,670,000	
	DS-2CD2T86G2-4I (2.8mm)	4K AcuSense Fixed Bullet Network Camera High quality imaging with 8 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light by 120 dB true WDR technology  Focus on human and vehicle targets classification based on deep learning	IRR 77,840,000	<b>6</b>
43	Exir Dome Series			
44	DS-2CD2327WD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 35,500,000	The state of the s
	DS-2CD2345FWD-I	Up to 2 megapixel high resolution - Full HD1080p video - Dual stream - 2.8mm/4mm/6mm fixed lens - 120dB Wide Dynamic Range - 3D Digital Noise Reduction - Backlight Compensation - DC12V & PoE - Support H.264+ - High performance EXIR LED - Up to 30m IR range - IP67 weather proof protection - 3-axis adjustment - Mobile Monitoring via EZVIZ P2P or Hik-Connect	IRR 45,950,000	Na state
45	Mini Dome Series			
46		1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - H.265+/H.265/H.264+/H.264/MJPEG - IR: up to 10 m 120dB		<b>6</b>
40	DS-2CD2523G0-IS	WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO	call	
47	DS-2CD2523G0-IS  DS-2CD2542FWD-IS		call	
		@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & POE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology		
	DS-2CD2542FWD-IS	@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection	call	
47	DS-2CD2542FWD-IS  DS-2CD2525FWD-I	@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection	call	
47	DS-2CD2542FWD-IS  DS-2CD2525FWD-I  Lite Bullet Vari-Facal Motorized S	@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & POE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection  eries  2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 ×1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264+, H.264Color: 0.01 Lux @ (F1.2,	call IRR 49,840,000	
47	DS-2CD2542FWD-IS  DS-2CD2525FWD-I  Lite Bullet Vari-Facal Motorized S  DS-2CD1623G0-I	@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & POE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W: Wi-Fi connection  eries  2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/R0I1920 ×1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB  2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/R0I1920 ×1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265+, H.264-, H.264Color: 0.01 Lux @ (F1.2, 1080@30fps - Up to 30 m IR range - IP67 - Up to 30 m IR range	call IRR 49,840,000 IRR 43,180,000	
47 48 49	DS-2CD2542FWD-IS  DS-2CD2525FWD-I  Lite Bullet Vari-Facal Motorized S  DS-2CD1623G0-I	@(F2.0, AGC ON), 0 lux with IR -S: Built-in MIC, audio/alarm IO  1/3" Progressive CMOS, ICR, 0lux with IR, 2688x1520:20fps, 4mm/F2.0 lens (2.8mm, 6mm optional), H.264+/H.264/MJPEG, VCA functions; 3 streams, IP67, DC12V & PoE, 120dB WDR, 3D DNR, BLC, IR: up to 10m, support on-board storage up to 128GB(SD card not included), HIK-Connect cloud service-S: Built-in MIC, audio/alarm IO  2 MP Powered-by-DarkFighter Fixed Mini Dome Network Camera High quality imaging with 2 MP resolution Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology -W·Wi-Fi connection  eries  2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 ×1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB  2MP Bullet Network camera - 2.8-12mm varifocal lens - EXIR - 1/2.8" progressive scan CMOS - BLC/3D DNR/ROI1920 ×1080@30fps - Up to 30 m IR range - IP67 - Digital WDR - H.265+, H.265, H.264+, H.264Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z:Motorized VF lens  4 MP EXIR VF Bullet Network Camera, 1/3" progressive scan CMOS - BLC/3D DNR/ROI - 2560 × 1440@20fps ,Up to 30 m IR range, 2.8 mm to 12 mm varifocal lens - IP67 - H.265+, H.265+, H.264+, H.264 - 120dB True WDR - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux@ (F1.6, AGC ON) - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB -	call IRR 49,840,000 IRR 43,180,000 call	

53	DS-2CD1743G0-IZ	4.0 MP VF Network Dome Camera-1/3" progressive scan CMOS - 3D DNR (Digital Noise Reduction) 2560 × 1440@20fps Up to 30 m IR range- 2.8 mm to 12 mm manual/motorized (with - PoE (Power over Ethernet)- IP67 H.265+, H.265, H.264+, H.264- Dual stream- 120 dB WDR (Wide Dynamic Range) - Z:Motorized VF lens	IRR 69,240,000	ASSESSOR
54	DS-2CD1753G0-I	5 MP Varifocal Dome Network Camera High quality imaging with 5 MP resolution,Efficient H.265+ compression technology Clear imaging even with strong back lighting due to 120 dB WDR, Up to 256 GB memory card slot for storage,2.8 to 12 mm motorized varifocal lens for easy installation and monitoring, Water and dust resistant (IP67) and vandal proof (IK10), EXIR 2.0: advanced infrared technology with long IR range	IRR 54,860,000	A51-25-7
55	<b>Bullet Vari-Facal Motorized Series</b>			
56	DS-2CD2625FWD-IZS	2MP Powered by DarkFighter Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Excellent low-light performance via powered-by-DarkFighter technology,Efficient H.265+compression technology,Clear imaging against strong back light due to 120 dB true WDR technology, Water and dust resistant (IP66) and vandal proof (IK10), Motorized varifocal lens for easy installation and monitoring full metal materials.	IRR 110,210,000	
57	DS-2CD2632F-I	3 MP IR VF Bullet Network Camera - 1/3" Progressive CMOS, ICR, Olux with IR, 2048×1536:25fps(P)/30fps(N), 2.8~12mm VF lens, H.264/MJPEG/H.264+, dual-stream, IP66, DC12V & PoE, DWDR, 3D DNR, BLC, IR: up to 30m, Support on-board card slot (SD card not included), Support Mobile Monitoring via EZVIZ P2P	IRR 60,500,000	
58	DS-2CD2643G2-IZS	4 MP WDR Motorized Varifocal Bullet Network Camera, High quality imaging with 4 MP resolution  Motorized varifocal lens for easy installation and monitoring  Clear imaging against strong backlight due to 120 dB WDR technology  Efficient H. 265+ compression technology, (IP67) and vandal resistant (IK10)  Focus on human and vehicle targets classification based on deep learning	IRR 96,030,000	
	DS-2CD2645FWD-IZS	High quality imaging with 4 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Water and dust resistant (IP66) and vandal proof (IK10)	IRR 92,660,000	
59	DS-2CD2663FG0-IZS	6 MP IR VF Bullet Network Camera - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - 1/2.9" Progressive Scan CMOS - 3072 × 2048@20 fps -2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - Z:Motorized VF lens	call	
60	DS-2CD2683G2-IZS	8 MP AcuSense Motorized Varifocal Bullet Network CameraHigh quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoringEfficient H.265+compression technology Clear imaging against strong backlight due to 120 dB true WDR technologyFocus on human and vehicle targets classification based on deep learningAudio and alarm interface availableWater and dust resistant (IP67) and vandal-resistant (IK10)	IRR 90,690,000	
DS	DS-2CD2685FWD-IZS	High quality imaging with 8 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Water and dust resistant (IP66) and vandal proof (IK10)	IRR 124,080,000	
61	DS-2CD2683G0-IZS	8 MP(4K) IR Vari-focal Bullet Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - IR Range up to 50m - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI • IP67, IK10 - Z:Motorized VF lens	call	
	DS-2CD2686G2-IZS (2.8-12mm)	High quality imaging with 8 MP resolution  Motorized varifocal lens for easy installation and monitoring  Excellent low-light performance via powered-by-DarkFighter technology  Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Focus on human and vehicle targets classification based on deep learning  Audio and alarm interface available  Water and dust resistant (IP66) and vandal proof (IK10)	IRR 118,340,000	
62	Dome Vari-Facal Motorized Series			
63	DS-2CD2743G2-IZS	4 MP Outdoor WDR Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolutionEfficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology-S: audio and alarm interface available- Water and dust resistant (IP67) and vandal proof (IK10)-Motorized varifocal lens for easy installation and monitoring- Robust structure design with full metal materials	IRR 97,950,000	MINION 3
	DS-2CD2745FWD-IZS	4 MP Powered-by-DarkFighter Varifocal Dome Network Camera High quality imaging with 4 MP resolution  Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology  Clear imaging against strong back light due to 120 dB true WDR technology  Water and dust resistant (IP66) and vandal proof (IK10)  Motorized varifocal lens for easy installation and monitoring	IRR 92,660,000	and the second s

64	DS-2CD2783G2-IZS	8 MP AcuSense Motorized Varifocal Dome Network Camera High quality imaging with 8 MP resolutionMotorized varifocal lens for easy installation and monitoring Efficient H.265+ compression technologyClear imaging against strong backlight due to 120 dB true WDR technologyFocus on human and vehicle targets classification based on deep learning Audio and alarm interface availableWater and dust resistant (IP67) and vandal-resistant (IK10)	IRR 83,742,500	- Contraction - State of the Contraction - State
65	DS-2CD2763G1-IZS	6 MP IR Vari-focal Dome Network Camera - 1/2.9" Progressive Scan CMOS - 3072 ×2048@20fps - 2.8 to 12 mm varifocal lens - Max IR distance: 30 meters - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detection - BLC/3D DNR/ROI - IP67, IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized VF lens	IRR 117,840,000	ALLEN S.
66	DS-2CD2783G0-IZS	8 MP(4K) IR Vari-focal Dome Network Camera - 1/2.5" Progressive Scan CMOS - 3840 ×2160@15fps - Max IR distance: 30 meters - 2.8 to 12 mm varifocal lens - Color: 0.01 Lux @ (F1.2, AGC ON), 0.018 Lux @ (F1.6, AGC ON), 0 Lux with IR - H.265+, H.265, H.264+, H.264 - 120dB WDR - 2 Behavior analyses, and face detectio - BLC/3D DNR/ROI - IP67 - IK10 - Built-in micro SD/SDHC/SDXC card slot, up to 128 GB - Z: Motorized  VF lens	call	and the second s
	DS-2CD2786G2-IZS	4K AcuSense Varifocal Dome Network Camera High quality imaging with 8 MP resolution Motorized varifocal lens for easy installation and monitoring Excellent low-light performance via powered-by-DarkFighter technology Efficient H.265+ compression technology Clear imaging against strong back light due to 120 dB true WDR technology Focus on human and vehicle targets classification based on deep learning Audio and alarm interface available Water and dust resistant (IP66) and vandal proof (IK10)	IRR 152,670,000	NA HEAVE
67	Fish Eye Series			
68	DS-2CD2955FWD-I	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range	IRR 126,380,000	G between the second se
	DS-2CD6332FWD-IS		IRR 178,300,000	
69	DS-2CD2955FWD-IS	5 MP Network Fisheye Camera,Up to 5 megapixel high resolution,2560 × 1920 @30fps,H.265, H.265+, H.264+, H.264, Support 14 display modes, FOV: horizontal FOV 180°, vertical FOV 180°, Dual video streams, DC12V & PoE (802.3af), Digital Noise Reduction, Support on-board storage, up to 128 GB, Up to 8m IR range, -S: Audio/Alarm IO	100,450,000	(G)
70	Cube Smart Series			
71	DS-2CD2420F-I(W)	Up to 2 megapixel (1920 × 1080 @ 30 fps) resolution - Standard video compression with high compression ratio, ROI (region of interest) encoding - Progressive scan CMOS - Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB- IR range approx. 10 meters - Two-way audio - Built-in microphone and speaker -Support Wi-Fi, support WPS configuration with one touch - Support PIR(Passive Infrared Detection) - IR cut filter with auto switch - Integrated mount for easy installation, Digital Wide Dynamic Range, Auto-electronic shutter	call	Out that
72	DS-2CD2421G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - <b>PIR: 10m -</b> H.265, H.265+ <b>DWDR</b> - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	IRR 28,480,000	
73	DS-2CD2423G0-IW	1/2.7" Progressive Scan CMOS - 1920 × 1080@30fps - IR: 10 m - <b>PIR: 10m -</b> H.265, H.265+ 120dB WDR - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - PoE - EXIR - Wi-Fi (Optional) - Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @ (F2.0, AGC ON), 0 lux with IR -W: Built-in Wi-Fi with WPS	call	ALLEY A
74	DS-2CD2443G0-IW	1/3" Progressive Scan CMOS - 2688 × 1520@30fps - IR: 10 m - PIR: 10m - 120dB WDR -Video Compression: H.265+/H.265/H.264+/H.264/MJPEG - Built-in Micro SD/SDHC/SDXC slot, up to 128 GB - Lens 2.8 mm, horizontal FOV: 98°, vertical FOV: 55° -W: Built-in Wi-Fi with WPS	IRR 39,375,000	
75	Pin Hole Series			
76	DS-2CD2D14WD	1 MP Pin Hole Camera - 1/4" Progressive CMOS, Electronic Day/night, Color: 0.01lux/F1.2, B/W: 0.001lux/F1.2, 1280x720: 25fps(P)/30fps(N), 3.6mm/F1.2 lens, H.264/MJPEG, dual-stream, DC12V, 100dB WDR, 3D DNR, BLC,  Support Mobile Monitoring via EZVIZ P2P	call	
77	2Q Smart Series			

78	DS-2CD2Q10FD-IW	1 MP CMOS PT Camera - 1/4" Progressive Scan CMOS - Up to 1.0 megapixel resolution - Support motorized Pan & Tilt - Digital WDR - 3D DNR - IR range approx. 10 meters - Support Wi-Fi, support WPS configuration with one touch (-W) - Two-way audio - Built-in microphone and speaker - Support 128G on-board storage - 5V DC±10% - Pan & Tilt Control Pan: 0° - 355°, Tilt: -20° - 90	IRR 31,300,000	P
79	2U Smart Series			
80	DS-2CV2U21FD-IW	2.0 MP Network Cube Camera - 1/2.8" Progressive CMOS, ICR, Olux with IR, 1920x1080: 25fps(P)/30fps(N), 2.8mm lens,H.264/MJPEG, dual-stream, 3D DNR, 5m IR, support on-board storage up to 128GB, HIK-Connect cloud service, Build-in microphone and speaker, support two-way audio. Built-in Wi-Fi, 12VDC power supply - 32GB-T: Include 32GB sd card.	IRR 21,790,000	
	People Counting			
	IDS-2CD6412FWD/C		IRR 224,880,000	
81	IP PTZ Camera			
82	DS-2DE4A225IW-DE	4-inch 2 MP 25X Powered by DarkFighter IR Network Speed Dome  High quality imaging with 2 MP resolution,Excellent low-light performance via powered-by, DarkFighter technology,  Clear imaging against strong back lighting due to 120 dB WDR technology, Pan and tilt ability enables camera to  monitor zones of interest,25x optical zoom allows for closer viewing of subjects in expansive areas,Up to 50m IR  range ensures safety at night (IP66)	IRR 124,900,000	ran d'Amer
83	DS-2DE4220IW-DE	2MP 20× Network IR Speed Dome - 1/3" CMOS sensor, H.264 codec, Color: 0.02lux/F1.5, B/W:0.02lux/F1.5, Optical Zoom:20x, Focus:4.7-94.0mm, Digital Zoom:16X, Pan range:360° endless; Tilt range: -15°~90°(Auto Flip), Pan Speed: 0.1° - 80°/s, Tilt Speed: 0.1° - 80°/s, 100m IR Distance, POE&12VDC	call	
84	DS-2DE4225IW-DE-S6	2MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 1920 × 1080@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with	157,470,000	
85	DS-2DE4425IW-DE T5	4MP 25× Network IR Speed Dome - 1/2.8" progressive scan CMOSUp to 2560 × 1440@30fps resolution-Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON)0 Lux with IR25× optical zoom Focal Length 4.8 mm to 120 mm - 16× digital zoom - WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus - Up to 100 m IR distance - 12 VDC & PoE+ (802.3 at, class4) Support H.265+/H.265 video compression - Excellent low-light performance with	210,020,000	
	DS-2DE5432IW-AE-S5	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome  1/2.8" Progressive Scan CMOS  High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  32× optical zoom, 16× digital zoom  WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus  Up to 150 m IR distance  Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm  Face capture: Up to 5 faces captured at the same time	229,040,000	
	DS-2DE5220IW-AE	DS-2DE5220IW-AE  2MP 20× Network IR Speed Dome  2.54cm(1/2.8") Progressive Scan CMOS  Up to 1920 × 1080 resolution  20× Optical Zoom, 16× Digital Zoom  Digital WDR  3D intelligent positioning function  Up to 150 m IR distance	231,170,000	
86	DS-2DE4A320IW-DE	3MP Network IR PTZ Camera 1/2.8" Progressive Scan CMOS  Up to 2048 × 1536 resolution  20× Optical Zoom, 16× Digital Zoom  WDR, 3D DNR, HLC, Smart IR  Up to 50 m IR distance  12 VDC & PoE+ (802.3at, class4)  Support H.265 video compression	IRR 274,170,000	
	DS-2DF6A236X-AEL	6-inch 2 MP 36X DarkFighter Network Speed Dome High quality imaging with 2 MP resolution Excellent low-light performance via DarkFighter technology 36x optical zoom provides close up views over expansive areas Intelligent functions based on deep learning Water and dust resistant (IP67) and vandal proof (IK10).	IRR 520,800,000	

87	DS-2CDE5432IW-AE	5-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome  1/2.8" Progressive Scan CMOS  High quality imaging with 4 MP resolution  Excellent low-light performance with powered-by-DarkFighter technology  32× optical zoom, 16× digital zoom  WDR, HLC, BLC, 3D DNR, Defog, Regional Exposure, Regional Focus, Rapid Focus  Up to 150 m IR distance  Accurate human and vehicle target classification, alarm, and linked tracking based on deep learning algorithm  Face capture: Up to 5 faces captured at the same time	IRR 229,050,000	
88	DS-2DE5230W-AE	2MP 30× Network IR Speed Dome - 1/2.8" CMOS, 3D DNR, ICR, Color: 0.05lux/F1.6, B/W:0.01lux/F1.6, Optical Zoom 30x, Focus:4.3-129.0mm, Digital Zoom:16X, 1920x1080:30fps, Pan Speed: 0.1° -250°/s, Tilt Speed: 0.1° -150°/s	call	
	DS-2CD5220IW-AE	2MP 20X Network IR PTZ Dome Camera  1920 x 1080, 1/2.8" Progressive Scan CMOS  20X Optical Zoom  DWDR  3D intelligent positioning function  Support cloud P2P  Up to 150m IR distance  Hi-PoE / 24VAC power supply	IRR 231,170,000	
	DS-2DF5276-AE3	2MP 20× Network Speed Dome , 1/2.8" Progressive Scan CMOS  Up to 1920 × 1080 resolution  20× Optical Zoom, 16× Digital Zoom  Digital WDR  3D intelligent positioning function  24 VAC & PoE+ (802.3at, class4)  Support H.265 video compression	IRR 562,530,000	· von
	DS-2DF5276-AEL	1.3MP 30X Network PTZ Dome Camera,  1/3" Progressive Scan CMOS  30X optical zoom, 16X digital zoom  Smart Tracking, Defog, ROI encoding, HLC  3-Streams  True Day/Night, 3D DNR, Digital WDR  3D intelligent positioning  High-PoE / PoE+ / 24VAC power supply	IRR 447,450,000	
	DS-2DE7232IW-AE	2MP 32× Network IR Speed Dome, Up to 1920 × 1080@60fps resolution,Min. illumination:  Color: 0.005 Lux @(F1.6, AGC ON),B/W: 0.001 Lux @(F1.6, AGC ON)  0 Lux with IR,32× optical zoom, 16× digital zoom, WDR, HLC, BLC, 3D DNR, Defog,EIS,Regional  Exposure, Regional Focus,Up to 150 m IR distance,24 VAC & Hi-PoE,Support H.265+/H.265 video compression	call	
89	DS-2DF8236I5W-AELW		IRR 1,143,020,000	
90	NVR-Monitor DS-7600NI-E1/A	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed	IRR 164,300,000	
92	NVR 4 Channel  DS-7104NI-Q1/M	IP video input : 4-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	26,860,000	***
94	DS-7104NI-Q1	4-ch Mini 1U NVR  H.265+/H.265/H.264+/H.264 video compression  Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth  Up to 4-ch network camera inputs  Up to 4-ch 1080p decoding capability  HDMI and VGA simultaneous output	IRR 20,290,000	
95	DS-7104NI-Q1/4P/M	IP video input: 4-ch / <b>4-ch POE</b> Up to 4 MP resolution - Decoding format: H.265+/H.265/ H.264+/H.264 - Incoming bandwidth: 40 Mbps - HDMI output: 1920 × 1080p/60Hz - Capacity: 1 SATA interface Up to 6TB capacity	call	

96	DS-7604NI-Q1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
97	DS-7604NI-Q1/4P	IP video input : 4-ch / <b>4-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
98	DS-7604NI-K1	IP video input : 4-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 50,140,000	
99	DS-7604NI-K1/4P	IP video input : 4-ch - <b>4-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 40 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 49,970,000	
100	NVR 8 Channel			
101	DS-7108NI-Q1/M	IP video input :8-ch Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 38,480,000	
102	DS-7108NI-Q1/8P/M	IP video input :8-ch / <b>8-ch POE</b> Up to 4 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 60 Mbps - HDMI output : 1920 × 1080p/60Hz - Capacity : 1 SATA interface Up to 6TB capacity	call	
103	DS-7608NI-Q2/8P	IP video input: 8-ch / 8-ch POE Up to 8 MP resolution - Decoding format: H.265+/H.265/ H.264+/H.264 - Incoming bandwidth: 80 Mbps - HDMI output: 4K (3840 × 2160)/30Hz - Capacity: 2 SATA interface Up to 6TB capacity for each disk	call	
	DS-7608NI-Q1		IRR 35,500,000	
104	DS-7608NI-Q2	Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	IRR 61,800,000	
105	DS-7608NI-K1	IP video input : 8-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 80 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	54,810,000	
106	DS-7608NI-K1/8P	8-ch 1U 8 PoE 4K NVR  Up to 8-ch IP camera inputs  H.265+/H.265/H.264+/H.264 video formats  Up to 1-ch@8 MP/3-ch@4 MP/6-ch@1080p decoding capacity  Up to 80 Mbps incoming bandwidth	IRR 69,090,000	
	DS-7608NI-K2	8-ch 1U 4K NVR  Up to 8-ch IP camera inputs  H.265+/H.265/H.264+/H.264 video formats  Up to 2-ch@8 MP or 4-ch@4 MP or 8-ch@1080p decoding capacity  1 HDMI and 1 VGA interfaces, both interfaces support independent video outpu  2 SATA interfaces for HDD connection (up to 10 TB capacity per HDD)  Up to 80 Mbps incoming bandwidth	52,280,000	
107	NVR 16 Channel			
108	DS-7616NI-Q1	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 1 SATA interface Up to 6TB capacity	IRR 48,200,000	
109	DS-7616NI-Q2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	69,950,000	
110	DS-7616NI-Q2/16P	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	IRR 107,470,000	
111	DS-7616NI-K1	Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 1-ch @ 8MP or 5-ch @ 1080P decoding capacity Up to 160 Mbps incoming bandwidth	IRR 46,781,000	
112	DS-7616NI-K2	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	78,210,000	

113	DS-7616NI-K2/16P	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 2 SATA interface Up to 6TB capacity for each disk	call	
114	DS-7716NI-Q4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 138,740,000	000
115	DS-7716NI-Q4/16P	IP video input : 16-ch / 16-ch POE Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 208,700,000	***
116	DS-7716NI-K4	IP video input : 16-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 119,640,000	2000 7.0
117	DS-7716NI-K4/16P	IP video input : 16-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 160 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	call	1000
118	Network Video Recorders- Ultra Seri	es		
119	DS-8616NI-K8	16-ch 2U 4K NVR,Up to 16 channel IP cameras can be connected,Supports decoding  H.265+/H.265/H.264+/H.264/MPEG4 video formats  Up to 4K high-definition live view, storage and playback, Up to 160 Mbps high incoming bandwidth ensures IP cameras can be connected,2 HDMI (different source) and 2 VGA (different source) interfaces,8 HDD can be used for continuous video recording Supports some specialist cameras, including people counting camera/ANRR (automatic	IRR 147,000,000	1100
120	NVR 32 Channel			
121	DS-7732NI-Q4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 200 Mbps - HDMI output : 1920 × 1080/60Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 119,500,000	***
122	DS-7732NI-Q4/16P	IP video input: 32-ch / <b>16-ch POE</b> Up to 8 MP resolution - Decoding format: H.265+/H.265/ H.264+/H.264 - Incoming bandwidth: 200 Mbps - HDMI output: 1920 × 1080/60Hz - Capacity: 4 SATA interface Up to 6TB capacity for each disk	IRR 170,000,000	100.
123	DS-7732NI-K4	IP video input : 32-ch Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	176,640,000	100
	IDS-7732NXI-14/8S	32-ch 1.5U 4K DeepinMind NVR  H.265+/H.265/H.264+/H.264 video formats  Intelligent analytics based on deep learning algorithm  Up to 16-ch perimeter protection  Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture  Up to 8-ch video structuralization  Up to 32-ch IP cameras can be connected  Up to 16-ch 1080p decoding capability	IRR 508,940,000	***
124	DS-7732NI-K4/16P	IP video input : 32-ch - <b>16-ch POE</b> Up to 8 MP resolution - Decoding format : H.265+/H.265/ H.264+/H.264 - Incoming bandwidth : 256 Mbps - HDMI output : 4K (3840 × 2160)/30Hz - Capacity : 4 SATA interface Up to 6TB capacity for each disk	IRR 265,500,000	1100
	DS-8632NI-K8		IRR 218,820,000	
	IDS-9632NXI-18/4F	32-ch 2U 4K DeepinMind NVR  H.265+/H.265/H.264+/H.264 video formats  Up to 32 channel IP cameras can be connected  8 HDD can be used for continuous video recording  Intelligent analytics based on deep learning algorithm  Up to 16-ch perimeter protection  Up to 8-ch facial recognition for video stream, or up to 16-ch facial recognition for face picture  Up to 4-ch video structuralization  Up to 16-ch 1080p decoding capability	IRR 2,274,450,000	***** = 0
	DS-9632NI-I8	32-ch 2U 4K NVR  Up to 32 channel IP cameras can be connected  Up to 12 MP high-definition live view, storage and playback  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  8 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition)  camera/fisheye camera  Advanced streaming technology enables smooth live view in poor network conditions  Supports RAID 0, 1, 5, 6, 10 and N+1 hot spare for even more reliable data storage, effectively avoids data loss risks	IRR 626,320,000	

DS-9632NI-I16	Up to 32 channel IP cameras can be connected  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  16 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition)  camera/fisheye camera	715,640,000	
DS-9664NI-18	Up to 64 channel IP cameras can be connected  Up to 12 MP high-definition live view, storage and playback  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  8 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition)	682,530,000	- D
DS-9664NI-I16	Up to 64 channel IP cameras can be connected  Up to 320 Mbps (or 200 Mbps when RAID is enabled) high incoming bandwidth ensures IP cameras can be connected  2 HDMI (different source) and 2 VGA (different source) interfaces  16 HDD can be used for continuous video recording  Supports some specialist cameras, including people counting camera/ANPR (automatic number plate recognition)  camera/fisheye camera	1,029,160,000	0.

D.D.C PERSIA
TelFax: 98 21 88 54 18 00
98 21 88 55 55 58
98 21 88 10 20 01 - 5
www.ddcpersia.com
info@ddcpersia.com